

Four Winns//2017

PRODUCT INFORMATION GUIDE





TABLE OF CONTENTS

HORIZON SERIES	PAGES
Horizon 180	4-7
Horizon 1800B.....	8-11
Freedom 190	12-13
Horizon 190	14-17
Horizon 200.....	18-21
Horizon 210	22-25
Horizon 230.....	26-31
Horizon 260.....	32-35
Horizon 290.....	36-41
Horizon 350.....	42-47
TS SERIES	
TS222	50-51
TS242	52-53
HD SERIES	
HD 220	56-59
HD 220 OB	60-63
HD 240	64-67
HD 240 OB	68-71
HD 270	72-75
HD 270 OB	76-79
VISTA SERIES	
Vista 255	82-85
Vista 275	86-89
Vista 335	90-93
Vista 355	94-97
Vista 375	98-101
TRAILERS	
Trailer Specifications	102-117
WARRANTY	
Warranty Information.....	118-128



HORIZON SERIES



HORIZON i80

Includes RS & SS

SPECIFICATIONS*	US	METRIC
LOA	18'0"	5.49 m
LOA w/extended Swim Platform	19'8"	6.00 m
Beam	7'7"	2.31 m
Fuel Capacity	24 gal	91 L
Draft (drive up)	16"	41 cm
Draft (drive down)	33"	84 cm
Maximum Capacity	1200 lbs	544 kg
Persons Capacity	8	6
Approx. Boat & Engine Weight	2550 lbs	1160 kg
Trailer Weight	861 lbs	390 kg
Deadrise	19°	19°
Storage Length on trailer	20'10"	6.35 m
Storage Length on trailer w/ext Swim	20'10"	6.35 m
Bridge Clearance	3'9"	1.14 m
Bridge Clearance RS/SS	3'6"	1.06 m
Bridge Clearance w/Arch	6'6"	1.97 m
Total Height	4'9"	1.45 m
Total Height RS/SS	4'6"	1.37 m
Total Height on Trailer	6'3"	1.91 m
Total Height on Trailer RS/SS	6'0"	1.83 m
Height on Trailer w/Wakeboard tower Dn	7'4"	2.23 m
Height on Trailer w/Wakeboard tower Up	9'0"	2.74 m

POWER RATINGS & WEIGHTS

Engine Type	Propshaft Power		Boat & Engine Weights	
	HP	KW	LBS	KG
MC 4.5L 200/A	200	149	2500	1130
MC 4.5L 250/A	250	187	2500	1130
VP V6-200/DI/SX	200	149	2430	1100
VP V6-240/DI/SX	240	179	2430	1100

RECOMMENDED ENGINE(S)/EQUIPMENT AVG. WEIGHTS

Model	Eng. Type	Boat	Eng.	Fuel	Access.	Trail Wt.
LBS						
H180	VP V6-200/DI	1590	840	144	100	861
KG						
H180	VP V6-200/DI	721	381	65	45	390



PERFORMANCE

Power HP/KW	Propeller (Dia x Pitch)		Type	Top Speed		Cruise Range	
	IN	CM		MPH	KPH	MI	KM
MC 4.5L 200/149/A	14 1/4 X 23	36 X 58	AL	48-51	77-82	90	145
MC 4.5L 250/187/A	14 1/2 X 19	37 X 48	AL	50-53	81-85	90	145
VP V6-200/149/DI/SX	14 1/4 X 21	36 X 53	AL	47-50	76-81	100	161
VP V6-240/179/DI/SX	14 1/4 X 21	36 X 53	AL	50-53	81-85	100	161

FUEL FLOW DATA - H180 W/ MC 4.5L 200/A

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	8	13	4	15
2500RPM	22	35	5	18
3000RPM	31	50	7	26
3500RPM	35	56	9	34
4000RPM	41	66	13	49
4500RPM	48	77	18	68
WOT	50	81	19	72

FUEL FLOW DATA - H180 W/ MC 4.5L 250/A

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	8	13	3	11
2500RPM	9	14	6	23
3000RPM	27	43	6	23
3500RPM	34	55	8	30
4000RPM	39	63	10	39
4500RPM	44	71	13	49
5000RPM	49	79	18	68
WOT	52	84	19	72

FUEL FLOW DATA - H180 W/ VP V6-200/DI/SX

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	7	11	3	11
2500RPM	11	18	5	19
3000RPM	15	24	6	23
3500RPM	28	45	6	23
4000RPM	33	53	7	26
4500RPM	37	60	9	34
5000RPM	42	68	12	45
5500RPM	47	76	16	60
WOT	49	79	18	68



FUEL FLOW DATA - H180 W/ VP V6-240/DI/SX

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	7	11	3	11
2500RPM	11	18	5	19
3000RPM	15	24	6	23
3500RPM	28	45	6	23
4000RPM	33	53	7	26
4500RPM	38	61	9	34
5000RPM	44	71	13	49
5500RPM	49	79	17	64
WOT	52	84	19	72

Performance and Fuel Flows may vary widely due to Boat Weight, Load, Atmospheric Conditions, Engine Conditions, Weight Distribution, Sea Conditions, Propeller, Boat Bottom Condition, Trim Angle and Operator Technique.



FAST FACTS NOTES



HORIZON 180 OB

Includes RS & SS

SPECIFICATIONS*	US	METRIC
LOA	17'11"	5.46 m
Beam	7'7"	2.31 m
Fuel Capacity	24 gal	91 L
Draft (drive up)	14"	36 cm
Draft (drive down)	31"	79 cm
Maximum Capacity	1800 lbs	816 kg
Persons Capacity	8	7
Approx. Boat & Engine Weight	2150 lbs	975 kg
Trailer Weight	639 lbs	290 kg
Deadrise	19°	19°
Storage Length on Trailer	21'2"	6.45 m
Bridge Clearance	3'9"	1.14 m
Bridge Clearance RS/SS	3'6"	1.06 m
Bridge Clearance w/Arch	6'6"	1.97 m
Total Height	4'9"	1.45 m
Total Height RS/SS	4'6"	1.37 m
Total Height on Trailer	6'3"	1.91 m
Total Height on Trailer RS/SS	6'0"	1.83 m
Height on Trailer w/Wakeboard Tower Dn	7'4"	2.23 m
Height on Trailer w/Wakeboard Tower Up	9'0"	2.74 m

POWER RATINGS & WEIGHTS

Engine Type	Propshaft Power		Boat & Engine Weights	
	HP	KW	LBS	KG
EVINRUDE 90 E-TEC	90	67	1940	880
EVINRUDE 115 E-TEC	115	86	1980	898
EVINRUDE 135HO E-TEC	135	101	2020	916
EVINRUDE 150 E-TEC	150	112	2020	916
MERCURY 90 EFI 4S	90	67	1980	898
MERCURY 115 EFI 4S	115	86	2000	907
MERCURY 150 EFI 4S	150	112	2060	934
YAMAHA 90 4S	90	67	1970	893
YAMAHA 115 4S	115	86	2010	912
YAMAHA 150 4S	150	112	2080	943

RECOMMENDED ENGINE(S)/EQUIPMENT AVG. WEIGHTS

Model	Eng. Type	Boat	Eng.	Fuel	Access.	Trail Wt.
LBS						
H1800B	Merc 115 4S	1600	400	144	100	639
KG						
H1800B	Merc 115 4S	726	181	65	45	290



PERFORMANCE

Power HP/KW	Propeller (Dia x Pitch)		Type	Top Speed		Cruise Range	
	IN	CM		MPH	KPH	MI	KM
EV 90 E-TEC/90/67	13 1/4 X 17	34 X 43	AL	38-41	61-66	110	180
EV 115 E-TEC/115/86	13 1/4 X 17	34 X 43	AL	41-44	66-71	110	180
EV 135 E-TEC/135/101	14.8 x 17	38 x 43	AL	44-47	71-76	95	155
EV 150 E-TEC/150/112	14.8 x 17	38 X 43	AL	45-48	72-77	110	180
Merc 90 4S/90/67	13 1/4 X 17	34 X 43	AL	38-41	61-66	110	180
Merc 115 4S/115/86	13 1/4 X 17	34 X 43	AL	41-44	66-71	120	190
Merc 150 4S/150/112	14 1/2 19	37 X 48	AL	47-50	76-81	120	190
Yamaha 90 4S/90/67	13 1/4 X 17	34 X 43	AL	38-41	61-66	110	180
Yamaha 115 4S/115/86	13 1/4 X 17	34 X 43	AL	41-44	66-71	110	180
Yamaha 150 4S/150/112	14 X 19	36 X 48	AL	47-50	76-81	120	190

FUEL FLOW DATA - H1800B W/ EVINRUDE 90 E-TEC/90/67 KW

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	7	11	1	4
2500RPM	8	13	2	8
3000RPM	10	16	3	11
3500RPM	20	32	4	15
4000RPM	25	40	5	19
4500RPM	29	47	7	26
5000RPM	34	55	8	30
WOT	38	61	9	34

FUEL FLOW DATA - H1800B W/ EVINRUDE 115 E-TEC/115/86 KW

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	7	11	1	4
2500RPM	8	13	3	8
3000RPM	10	16	4	11
3500RPM	20	32	5	19
4000RPM	25	40	6	23
4500RPM	30	48	8	30
5000RPM	35	56	9	34
5500RPM	40	64	10	38
WOT	41	66	11	42

FUEL FLOW DATA - H1800B W/ EVINRUDE 135HO E-TEC/130/101 KW

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	7	11	2	8
2500RPM	10	16	5	19
3000RPM	21	34	6	23
3500RPM	27	43	7	26
4000RPM	32	52	8	30
4500RPM	37	60	11	42
5000RPM	40	64	13	49
WOT	45	72	14	53

**FUEL FLOW DATA - H1800B W/ EVINRUDE 150 E-TEC/150/112 KW**

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	7	11	2	8
2500RPM	10	16	5	19
3000RPM	21	34	6	23
3500RPM	27	43	7	26
4000RPM	32	52	8	30
4500RPM	37	60	11	42
5000RPM	41	66	13	49
WOT	45	72	15	57

FUEL FLOW DATA - H1800B W/ MERCURY 90 4S/90/67 KW

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	6	10	1	4
2500RPM	7	11	2	8
3000RPM	8	13	3	11
3500RPM	13	21	4	15
4000RPM	22	35	4	15
4500RPM	27	43	6	23
5000RPM	31	50	6	23
5000RPM	35	56	7	26
WOT	38	61	9	34

FUEL FLOW DATA - H1800B W/ MERCURY 115 4S/115/86 KW

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	6	10	1	4
2500RPM	7	11	2	8
3000RPM	8	13	3	11
3500RPM	13	21	4	15
4000RPM	22	35	5	19
4500RPM	28	45	6	23
5000RPM	33	53	7	26
5500RPM	38	61	9	34
WOT	41	66	11	42

FUEL FLOW DATA - H1800B W/ MERCURY 150 4S/150/112 KW

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	8	13	2	8
2500RPM	10	16	4	15
3000RPM	23	37	4	15
3500RPM	28	45	5	19
4000RPM	33	53	7	26
4500RPM	39	63	10	38
5000RPM	42	68	11	42
5500RPM	47	76	13	49
WOT	48	77	14	53

**FUEL FLOW DATA - H1800B W/ YAMAHA 90 4S/90/67 KW**

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	8	13	2	8
2500RPM	10	16	4	15
3000RPM	23	37	4	15
3500RPM	28	45	5	19
4000RPM	33	53	7	26
4500RPM	39	63	10	38
5000RPM	42	68	11	42
5500RPM	47	76	13	49
WOT	48	77	14	53

FUEL FLOW DATA - H1800B W/ YAMAHA 115 4S/115/86 KW

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	6	10	1	4
2500RPM	7	11	2	8
3000RPM	9	14	3	11
3500RPM	16	26	4	15
4000RPM	23	37	5	19
4500RPM	29	47	6	23
5000RPM	34	55	8	30
5500RPM	39	63	10	38
WOT	41	66	11	42

FUEL FLOW DATA - H1800B W/ YAMAHA 150 4S/150/112 KW

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	8	13	2	8
2500RPM	10	16	4	15
3000RPM	22	35	4	15
3500RPM	28	45	5	19
4000RPM	33	53	7	26
4500RPM	38	61	9	34
5000RPM	41	66	11	42
5500RPM	46	74	13	49
WOT	47	76	15	57

Performance and Fuel Flows may vary widely due to Boat Weight, Load, Atmospheric Conditions, Engine Conditions, Weight Distribution, Sea Conditions, Propeller, Boat Bottom Condition, Trim Angle and Operator Technique.



FREEDOM 190

SPECIFICATIONS*

	US	METRIC
LOA	19'0"	5.79 m
Beam	7'11"	2.41 m
Fuel Capacity	32 gal	121 L
Draft (drive up)	16"	41 cm
Draft (drive down)	33"	84 cm
Maximum Capacity	1400 lbs	635 kg
Persons Capacity	9	8
Approx. Boat & Engine Weight	2800 lbs	1220 kg
Trailer Weight	803 lbs	364 kg
Deadrise	20°	20°
Storage Length on Trailer	20'9"	6.32 m
Bridge Clearance	3'10"	1.17 m
Total Height	5'0"	1.52 m
Total Height on Trailer	6'6"	1.98 m

POWER RATINGS & WEIGHTS

Engine Type	Propshaft Power		Boat & Engine Weights	
	HP	KW	LBS	KG
VP V6-200/SX	200	145	2600	1180
VP V6-200/SX DI	200	145	2600	1180

RECOMMENDED ENGINE(S)/EQUIPMENT AVG. WEIGHTS

Model	Eng. Type	Boat	Eng.	Fuel	Access
LBS					
F190	VP V6-200 DI	1750	910	192	100
KG					
F190	VP V6-200 DI	794	413	87	45

PERFORMANCE

Power HP/ kW	Propeller (Dia x Pitch)		Type	Top Speed		Cruise Range	
	IN	CM		MPH	KPH	MI	KM
VP V6-200/SX	14 1/4 X 21	36 X 53	AL	44-47	71-76	115	185
VP V6-200/DI/SX	14 1/4 X 21	36 X 53	AL	44-47	71-76	125	200



FUEL FLOW DATA - F190 W/VP V6-200/SX

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	7	11	3	11
2500RPM	11	18	5	19
3000RPM	14	23	6	23
3500RPM	17	43	7	26
4000RPM	31	50	8	30
4500RPM	35	56	10	38
5000RPM	40	64	12	45
5500RPM	44	71	16	60
WOT	46	74	18	68

FUEL FLOW DATA - F190 W/ VP V6-200/DI/SX

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	8	13	4	15
2500RPM	10	16	6	23
3000RPM	15	24	7	26
3500RPM	24	39	8	30
4000RPM	29	47	9	35
4500RPM	33	53	11	42
5000RPM	38	63	12	45
5500RPM	43	69	14	53
WOT	45	72	16	60

Performance and Fuel Flows may vary widely due to Boat Weight, Load, Atmospheric Conditions, Engine Conditions, Weight Distribution, Sea Conditions, Propeller, Boat Bottom Condition, Trim Angle and Operator Technique.



HORIZON 190

Includes RS & SS

SPECIFICATIONS*	US	METRIC
LOA	19'0"	5.79 m
LOA w/ext Swim Platform	20'8"	6.30 m
Beam	7'11"	2.41 m
Fuel Capacity	32 gal	121 L
Draft (drive up)	16"	41 cm
Draft (drive down)	33"	84 cm
Maximum Capacity	1400 lbs	635 kg
Persons Capacity	9	8
Approx. Boat & Engine Weight	2800 lbs	1220 kg
Trailer Weight	861(S)/1123(T) lbs	391(S)/509(T) kg
Deadrise	20°	20°
Storage Length on Trailer	20'9"	6.32 m
Storage Length on Trailer w/ext Swim	21'2"	6.45 m
Bridge Clearance	3'10"	1.17 m
Bridge Clearance RS/SS	3'7"	1.09 m
Bridge Clearance with arch/tower	6'0"	2.06 m
Total Height	5'0"	1.52 m
Total Height RS/SS	4'9"	1.45 m
Total Height on Trailer	6'6"	1.98 m
Total Height on Trailer RS/SS	6'3"	1.91 m
Height on Trailer w/Wakeboard Tower Dn	8'4"	2.54 m
Height on Trailer w/Wakeboard Tower Up	9'5"	2.87 m

POWER RATINGS & WEIGHTS

Engine Type	Propshaft Power		Boat & Engine Weights	
	HP	KW	LBS	KG
MC 4.5L 200/A	200	145	2660	1210
MC 4.5L 250/A	250	187	2660	1210
VP V6-200/DI/SX	200	145	2600	1180
VP V6-240/DI/SX	240	179	2600	1180

RECOMMENDED ENGINE(S)/EQUIPMENT AVG. WEIGHTS

Model	Eng. Type	Boat	Eng.	Fuel	Access.	Trail Wt.
LBS						
H190	VP V6-240 DI	1750	910	192	100	861(S) 1,123(T)
KG						
H190	VP V6-240 DI	794	413	87	45	390(S) 509(T)



PERFORMANCE

Power HP/KW	Propeller (Dia x Pitch)		Type	Top Speed		Cruise Range	
	IN	CM		MPH	KPH	MI	KM
MC 4.5L/A/200	14 1/2 X 19	37 X 48	AL	42-45	68-72	115	185
MC 4.5L/A 250/187	14 1/2 X 19	37 X 48	AL	48-51	77-82	110	180
VP V6-200/DI/SX	14 1/4 X 21	36 X 53	AL	44-47	71-76	125	200
VP V6-240/DI/SX	14 1/4 X 21	36 X 53	AL	47-50	76-81	125	200

FUEL FLOW DATA - H190 W/MC 4.5L 200/A

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	8	13	4	15
2500RPM	10	16	7	26
3000RPM	26	42	8	30
3500RPM	32	52	10	38
4000RPM	36	58	13	49
4500RPM	41	66	15	57
WOT	44	71	16	60

FUEL FLOW DATA - H190 W/ MC 4.5L 250/A

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	7	11	3	11
2500RPM	9	14	6	23
3000RPM	25	40	7	26
3500RPM	31	50	8	30
4000RPM	36	58	10	38
4500RPM	41	66	13	49
5000RPM	47	76	18	68
WOT	49	79	19	72

FUEL FLOW DATA - H190 W/ VP V6-200/DI/SX

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	8	13	4	15
2500RPM	10	16	6	23
3000RPM	15	24	7	26
3500RPM	24	39	8	30
4000RPM	29	47	9	35
4500RPM	33	53	11	42
5000RPM	38	63	12	45
5500RPM	43	69	14	53
WOT	45	72	16	60



FUEL FLOW DATA - H190 W/VP V6-240/DI/SX

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	8	13	3	11
2500RPM	10	16	6	23
3000RPM	15	24	7	26
3500RPM	24	39	8	30
4000RPM	29	47	9	35
4500RPM	34	55	11	42
5000RPM	40	64	12	45
5500RPM	45	72	14	53
WOT	49	79	18	68

Performance and Fuel Flows may vary widely due to Boat Weight, Load, Atmospheric Conditions, Engine Conditions, Weight Distribution, Sea Conditions, Propeller, Boat Bottom Condition, Trim Angle and Operator Technique.



FAST FACTS NOTES



HORIZON 200

Includes RS & SS

SPECIFICATIONS*

	US	METRIC
LOA	20'1"	6.12 m
LOA w/Extended Swim Platform	21'9"	6.63 m
Beam	8'3"	2.5 m
Fuel Capacity	32 gal	121 L
Draft (drive up)	16"	41 cm
Draft (drive down)	33"	84 cm
Maximum Capacity	1500 lbs	680 kg
Persons Capacity	9	8
Approx. Boat & Engine Weight	3050 lbs	1380 kg
Trailer Weight	894 (S)/1101(T) lbs	406(S)/499(T) kg
Deadrise	20°	20°
Storage Length on Trailer	20'10"	6.35 m
Storage Length on Trailer w/Extended Swim	21'9"	6.63 m
Bridge Clearance	4'0"	1.22 m
Bridge Clearance RS/SS	3'9"	1.14 m
Bridge Clearance with Arch/Tower	7'5"	2.31 m
Total Height	5'2"	1.58 m
Total Height RS/SS	4'11"	1.50 m
Total Height on Trailer	6'6"	1.98 m
Total Height on Trailer RS/SS	6'3"	1.88 m
Height on Trailer w/Wakeboard Tower Dn	8'4"	2.54 m
Height on Trailer w/Wakeboard Tower Up	10'1"	3.07 m

POWER RATINGS & WEIGHTS

Engine Type	Propshaft Power		Boat & Engine Weights	
	HP	KW	LBS	KG
MC 4.5L 200/A	200	149	3020	1370
MC 4.5L 250/A	250	187	3020	1370
MC 6.2L 300/B1	300	224	3200	1450
VP V6-200/DI/SX	200	149	2960	1340
VP V6-240/DI/SX	240	179	2960	1340
VP V6-280/DI/SX	280	209	2960	1340
VP V8-300/DI/SX	300	224	3050	1380

RECOMMENDED ENGINE(S)/EQUIPMENT AVG. WEIGHTS

Model	Eng. Type	Boat	Eng	Fuel	Access.	Trail Wt.
LBS						
H200	VP V6-280 DI	2060	900	192	100	894(S)1,101(T)
KG						
H200	VP V6-280 DI	934	408	87	45	406(S) 500(T)



PERFORMANCE

Power HP/KW	Propeller (Dia x Pitch)		Type	Top Speed		Cruise Range	
	IN	CM		MPH	KPH	MI	KM
MC 4.5L 200/149/A	14 1/2 X 19	37 X 48	AL	43-46	69-74	115	185
MC 4.5L 250/187/A	14 1/2 X 19	37 X 48	AL	47-50	76-81	115	185
MC 6.2L 300/224/B1	14 X 19	36 X 48	SST	53-56	85-90	115	185
VP V6-200/149/DI/SX	14 1/2 x 19	37-X 48	AL	42-45	68-72	125	200
VP V6-240/179/DI/SX	14 1/2 x 19	37-X 48	AL	46-49	74-79	125	200
VP V6-280/209/DI/SX	14 1/4 X 21	36 X 53	AL	50-53	81-85	125	200
VP V8-300/224/DI/SX	14 3/4 X 19	37 X 48	SST	52-55	84-89	125	200

FUEL FLOW DATA - H200 W/ MC 4.5L 200/A

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	8	13	4	15
2500RPM	22	35	5	19
3000RPM	29	47	7	26
3500RPM	35	56	9	34
4000RPM	40	64	13	49
4500RPM	41	66	15	57
WOT	45	72	16	60

FUEL FLOW DATA - H200 W/ MC 4.5L 250/A

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	7	11	3	11
2500RPM	9	14	5	19
3000RPM	23	37	7	26
3500RPM	30	48	8	30
4000RPM	36	58	10	38
4500RPM	41	66	13	49
5000RPM	46	74	18	68
WOT	48	77	19	72

FUEL FLOW DATA - H200 W/MC 6.2L 300/B1

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	8	13	3	11
2500RPM	10	16	6	23
3000RPM	14	23	12	45
3500RPM	26	42	13	49
4000RPM	34	55	15	57
4500RPM	42	68	18	68
5000RPM	49	79	21	79
WOT	54	87	23	87



FUEL FLOW DATA - H200 W/VP V6-200/DI/SX

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	8	13	4	15
2500RPM	10	16	6	23
3000RPM	15	24	7	26
3500RPM	24	39	8	30
4000RPM	29	47	9	35
4500RPM	33	53	11	42
5000RPM	37	60	12	45
5500RPM	42	68	14	53
WOT	43	69	16	60

FUEL FLOW DATA - H200 W/VP V6-240/DI/SX

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000 RPM	8	13	3	11
2500RPM	10	16	6	23
3000RPM	15	24	7	26
3500RPM	24	39	8	30
4000RPM	29	47	9	35
4500RPM	34	55	11	42
5000RPM	40	64	12	45
5500RPM	44	71	14	53
WOT	47	76	18	68

FUEL FLOW DATA - H200 W/VP V6-280/DI/SX

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	8	13	3	11
2500RPM	10	16	6	23
3000RPM	15	24	7	26
3500RPM	24	39	8	30
4000RPM	29	47	9	35
4500RPM	34	55	11	42
5000RPM	41	66	13	49
5500RPM	47	76	16	60
WOT	52	84	21	79



FUEL FLOW DATA - H200 W/VP V8-300/DI/SX

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	8	13	3	11
2500RPM	10	16	6	23
3000RPM	15	24	7	26
3500RPM	24	39	8	30
4000RPM	29	47	10	38
4500RPM	35	56	12	45
5000RPM	42	68	15	57
5500RPM	49	79	18	68
WOT	54	87	23	87

Performance and Fuel Flows may vary widely due to Boat Weight, Load, Atmospheric Conditions, Engine Conditions, Weight Distribution, Sea Conditions, Propeller, Boat Bottom Condition, Trim Angle and Operator Technique.



HORIZON 210

Includes RS & SS

SPECIFICATIONS*	US	METRIC
LOA	21'7"	6.58 m
Beam	8'5"	2.55 m
Fuel Capacity	40 gal	151 L
Draft (drive up)	16"	40 cm
Draft (drive down)	33"	83 cm
Maximum Capacity	1600 lbs	725 kg
Persons Capacity	10	9
Approx. Boat & Engine Weight	3450 lbs	1560 kg
Trailer Weight	1196 lbs	543 kg
Deadrise	20°	20°
Storage Length on Trailer	21'7"	6.58 m
Bridge Clearance	4'4"	1.32 m
Bridge Clearance RS/SS	4'1"	1.24 m
Bridge Clearance with Arch/Tower	7'4"	2.24 m
Total Height	5'4"	1.63 m
Total Height RS/SS	5'1"	1.55 m
Total Height on Trailer	7'0"	2.13 m
Total Height on Trailer RS/SS	6'9"	2.06 m
Height on Trailer w/Wakeboard Tower Dn	8'6"	2.59 m
Height on Trailer w/Wakeboard Tower Up	10'0"	3.05 m
Potable Water (standard or optional)	12 gal	45 L

POWER RATINGS & WEIGHTS

Engine Type	Propshaft Power		Boat & Engine Weights	
	HP	KW	LBS	KG
MC 4.5L 250/A	250	187	3380	1530
MC 4.5L 250/B3	250	187	3400	1540
MC 6.2L 300/B1	300	224	3480	1580
MC 6.2L 300/B3	300	224	3500	1590
VP V6-240/DI/SX	240	179	3180	1440
VP V6-240/DI/DP	240	179	3200	1450
VP V6-280/DI/SX	280	209	3180	1440
VP V6-280/DI/DP	280	209	3200	1450
VP V8-300/DI/SX	300	224	3280	1490
VP V8-300/DI/DP	300	224	3300	1500

RECOMMENDED ENGINE(S)/EQUIPMENT AVG. WEIGHTS

Model	Eng. Type	Boat	Eng.	Fuel	Access.	Trail Wt.
LBS						
H210	VP V6-280 DI	2290	900	240	150	1051(S)/1234(T)
KG						
H210	VP V6-280 DI	1040	409	109	68	477(S)/560(T)



PERFORMANCE

Power HP/KW	Propeller (Dia x Pitch)		Type	Top Speed		Cruise Range	
	IN	CM		MPH	KPH	MI	KM
MC 4.5L 250/187/A	15 X 17	38 x 43	AL	43-46	69-74	120	190
MC 4.5L 250/187/B3	24	61	SST	45-48	72-77	120	190
MC 6.2L 300/224/B1	15 1/2 X 17	39 X 43	SST	49-52	79-84	120	190
MC 6.2L 300/224/B3	24	61	SST	50-53	81-87	120	190
VP V6-240/179/DI/SX	15 X 17	38 x 43	AL	41-44	66-71	135	215
VP V6-240/179/DI/DP	FH4	FH4	SST	43-46	69-74	135	215
VP V6-280/209/DI/SX	14 1/2 X 19	37 x 48	AL	47-50	76-81	135	215
VP V6-280/209/DI/DP	FH4	FH4	SST	48-51	77-82	135	215
VP V8-300C/224/DI/SX	14 3/4" x 17"	37 x 43	SST	49-52	79-84	130	210
VP V8-300C/224/DI/DP	FH5	FH5	SST	50-53	81-87	130	210

FUEL FLOW DATA - H210 W/ MC 4.5L 250/A

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	8	13	3	11
2500RPM	10	16	5	19
3000RPM	23	37	6	23
3500RPM	30	48	7	26
4000RPM	35	56	10	38
4500RPM	40	64	13	49
5000RPM	43	69	17	64
WOT	44	71	18	68

FUEL FLOW DATA - H210 W/ MC 4.5L 250/B3

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	8	13	3	11
2500RPM	10	16	5	19
3000RPM	23	37	6	23
3500RPM	31	50	7	26
4000RPM	36	58	9	34
4500RPM	42	68	12	45
5000RPM	45	72	17	64
WOT	46	74	18	68

FUEL FLOW DATA - H210 W/MC 6.2L 300/B1

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	8	13	3	11
2500RPM	10	16	6	23
3000RPM	14	23	11	42
3500RPM	27	44	12	45
4000RPM	32	52	14	53
4500RPM	40	64	18	68
5000RPM	46	74	21	75
WOT	51	82	23	87



FUEL FLOW DATA - H210 W/MC 6.2L 300/B3

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	8	13	3	11
2500RPM	10	16	6	23
3000RPM	14	23	11	42
3500RPM	27	43	12	45
4000RPM	33	53	14	53
4500RPM	41	68	18	68
5000RPM	47	76	21	75
WOT	52	84	23	87

FUEL FLOW DATA - H210 W/VP V6-240/DI/SX

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	8	13	3	11
2500RPM	10	16	6	23
3000RPM	15	24	7	26
3500RPM	24	39	8	30
4000RPM	29	47	9	35
4500RPM	34	55	11	42
5000RPM	38	61	12	45
5500RPM	41	66	14	53
WOT	43	69	18	68

FUEL FLOW DATA - H210 W/VP V6-240/DI/DP

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	8	13	3	11
2500RPM	10	16	6	23
3000RPM	15	24	7	26
3500RPM	24	39	8	30
4000RPM	30	48	9	35
4500RPM	35	56	11	42
5000RPM	39	62	12	45
5500RPM	43	69	14	53
WOT	45	72	18	68

FUEL FLOW DATA - H210 W/VP V6-280/DI/SX

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	8	13	3	11
2500RPM	10	16	6	23
3000RPM	15	24	7	26
3500RPM	24	39	8	30
4000RPM	28	45	9	35
4500RPM	32	52	11	42
5000RPM	39	63	13	49
5500RPM	44	71	16	60
WOT	49	79	21	79



FUEL FLOW DATA - H210 W/VP V6-280/DI/DP

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	8	13	3	11
2500RPM	10	16	6	23
3000RPM	15	24	7	26
3500RPM	24	39	8	30
4000RPM	28	45	9	35
4500RPM	32	52	11	42
5000RPM	39	63	13	49
5500RPM	45	72	16	60
WOT	50	81	21	79

FUEL FLOW DATA - H210 W/VP V8-300C/DI/SX

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	8	13	3	11
2500RPM	10	16	6	23
3000RPM	15	24	7	26
3500RPM	24	39	8	30
4000RPM	28	45	10	38
4500RPM	33	53	12	45
5000RPM	40	64	15	57
5500RPM	46	74	18	68
WOT	51	82	23	87

FUEL FLOW DATA - H210 W/VP V8-300C/DI/DP

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	8	13	3	11
2500RPM	10	16	6	23
3000RPM	15	24	7	26
3500RPM	24	39	8	30
4000RPM	28	45	10	38
4500RPM	33	53	12	45
5000RPM	40	64	15	57
5500RPM	47	76	18	68
WOT	52	84	23	87

Performance and Fuel Flows may vary widely due to Boat Weight, Load, Atmospheric Conditions, Engine Conditions, Weight Distribution, Sea Conditions, Propeller, Boat Bottom Condition, Trim Angle and Operator Technique.



HORIZON 230

Includes RS & SS

SPECIFICATIONS*	US	METRIC
LOA	23'7"	7.19 m
Beam	8'5"	2.55 m
Fuel Capacity	52 gal	197 L
Draft (drive up)	16"	40 cm
Draft (drive down)	33"	83 cm
Maximum Capacity	1800 lbs	816 kg
Persons Capacity	11	10
Approx. Boat & Engine Weight	3850 lbs	1840 kg
Trailer Weight	1505 lbs	683 kg
Deadrise	20°	20°
Storage Length on Trailer	23'7"	7.19 m
Bridge Clearance	4'5"	1.35 m
Bridge Clearance RS/SS	4'2"	1.27 m
Bridge Clearance with Arch/Tower	7'5"	2.27 m
Total Height	5'6"	1.68 m
Total Height RS/SS	5'3"	1.60 m
Total Height on Trailer	7'2"	2.18 m
Total Height on Trailer RS/SS	6'11"	2.11 m
Height on Trailer w/Wakeboard Tower Dn	8'10"	2.69 m
Height on Trailer w/Wakeboard Tower Up	10'2"	3.10 m
Potable Water (standard or optional)	12 gal	45 L

POWER RATINGS & WEIGHTS

Engine Type	Propshaft Power		Boat & Engine Weights	
	HP	KW	LBS	KG
MC 4.5L 250/A	250	187	4270	1940
MC 4.5L 250/B3	250	187	4300	1950
MC 6.2L 300/B3	300	224	4400	2000
MC 6.2L 350/B3	350	261	4400	2000
MC 6.2L 350/B3/DTS	350	261	4400	2000
VP V6-280/DI/SX	280	209	4070	1850
VP V6-280/DI/DP	280	209	4200	1900
VP V8-300C/DI/SX	300	224	4170	1890
VP V8-300C/DI/DP	300	224	4200	1900
VP V8-350C/DI/DP	350	261	4200	1900
VP V8-350CE/DI/DP/EVC	350	261	4200	1900
VP V8-380CE/DP EVC	380	280	4350	1970

RECOMMENDED ENGINE(S)/EQUIPMENT AVG. WEIGHTS

Model	Eng. Type	Boat	Eng.	Fuel	Access.	Trail Wt.
LBS						
H230	VP V8-300 DI/DP	3200	1000	310	150	1505
KG						
H230	VP V8-300 DI/DP	1450	454	141	68	683



PERFORMANCE

Power HP/KW	Propeller (Dia x Pitch)		Type	Top Speed		Cruise Range	
	IN	CM		MPH	KPH	MI	KM
MC 4.5L 250/187/A	15 1/4 X 15	39 X 36	AL	39-42	63-68	130	210
MC 4.5L 250/187/B3	22 1/2	57	SST	41-44	68-71	130	210
MC 6.2L 300/224/B3	24	61	SST	46-49	74-79	130	210
MC 6.2L 350/261/B3	24	61	SST	50-53	81-85	130	210
MC 6.2L 350/216/B3/DTS	24	61	SST	50-53	81-85	130	210
VP V6-280/209/DI/SX	15 X 17	36 x 43	AL	42-45	65-72	150	240
VP V6-280/209/DI/DP	FH4	FH4	SST	43-46	69-74	150	240
VP V8-300C/224/DI/SX	14 3/4 X 17	37 X 43	SST	45-48	72-77	150	240
VP V8-300C/224/DI/DP	FH4	FH4	SST	46-49	74-79	150	240
VP V8-350C/261/DI/DP	FH5	FH5	SST	51-54	82-87	150	240
VP V8-350CE/261/DI/DP/EVC	FH5	FH5	SST	51-54	82-87	150	240
VP V8-380CE/283/DP/EVC	FH5	FH5	SST	53-56	85-90	140	225

FUEL FLOW DATA - H230 W/MC 4.5L 250/A

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	8	13	3	11
2500RPM	10	16	5	19
3000RPM	22	35	6	23
3500RPM	29	47	7	26
4000RPM	33	53	10	38
4500RPM	38	61	13	49
5000RPM	40	64	17	64
WOT	41	66	18	68

FUEL FLOW DATA - H230 W/MC 4.5L 250/B3

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	8	13	3	11
2500RPM	10	16	5	19
3000RPM	22	35	6	23
3500RPM	29	47	7	26
4000RPM	34	55	10	38
4500RPM	39	63	13	49
5000RPM	42	68	17	64
WOT	43	69	18	68

FUEL FLOW DATA - H230 W/MC 6.2L 300/B3

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	8	13	3	11
2500RPM	10	16	6	23
3000RPM	14	23	11	42
3500RPM	26	42	12	45
4000RPM	31	50	14	53
4500RPM	38	61	18	68
5000RPM	44	71	21	75
WOT	48	77	23	87

**FUEL FLOW DATA - H230 W/MC 6.2L 350/B3**

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	9	14	4	15
2500RPM	16	26	7	27
3000RPM	24	39	10	38
3500RPM	30	48	12	45
4000RPM	37	60	15	57
4500RPM	44	71	18	70
5000RPM	49	79	22	85
WOT	52	84	26	99

FUEL FLOW DATA - H230 W/MC 6.2L 350/B3/DTS

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	9	14	4	15
2500RPM	16	26	7	27
3000RPM	24	39	10	38
3500RPM	30	48	12	45
4000RPM	37	60	15	57
4500RPM	44	71	18	70
5000RPM	49	79	22	85
WOT	52	84	26	99

FUEL FLOW DATA - H230 W/ VP V6-280/DI/SX

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	8	13	3	11
2500RPM	10	16	6	23
3000RPM	15	24	7	26
3500RPM	24	39	8	30
4000RPM	27	43	9	35
4500RPM	30	48	11	42
5000RPM	36	58	13	49
5500RPM	40	64	16	60
WOT	44	71	21	79

FUEL FLOW DATA - H230 W/ VP V6-280/DI/DP

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	8	13	3	11
2500RPM	10	16	6	23
3000RPM	15	24	7	26
3500RPM	24	39	8	30
4000RPM	27	43	9	35
4500RPM	30	48	11	42
5000RPM	36	58	13	49
5500RPM	40	64	16	60
WOT	45	72	21	79

**FUEL FLOW DATA - H230 W/VP V8-300C/DI/SX**

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	8	13	3	11
2500RPM	10	16	6	23
3000RPM	15	24	7	26
3500RPM	23	37	8	30
4000RPM	26	42	10	38
4500RPM	30	48	12	45
5000RPM	37	60	15	57
5500RPM	42	68	18	68
WOT	47	76	23	87

FUEL FLOW DATA - H230 W/VP V8-300C/DI/DP

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	8	13	3	11
2500RPM	10	16	6	23
3000RPM	15	24	7	26
3500RPM	23	37	8	30
4000RPM	26	42	10	38
4500RPM	31	50	12	45
5000RPM	37	60	15	57
5500RPM	44	71	18	68
WOT	48	77	23	87

FUEL FLOW DATA - H230 W/VP V8-350C/DI/DP

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	8	13	3	11
2500RPM	10	16	6	23
3000RPM	15	24	7	26
3500RPM	24	39	8	30
4000RPM	28	45	10	38
4500RPM	33	53	13	49
5000RPM	40	64	17	64
5500RPM	47	76	21	79
WOT	52	84	26	98

FUEL FLOW DATA - H230 W/VP V8-350CE/DI/DP/EVC

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	8	13	3	11
2500RPM	10	16	6	23
3000RPM	15	24	7	26
3500RPM	24	39	8	30
4000RPM	28	45	10	38
4500RPM	33	53	13	49
5000RPM	40	64	17	64
5500RPM	47	76	21	79
WOT	52	84	26	98



FUEL FLOW DATA - H230 W/VP V8-380CE/DP EVC

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	8	13	4	15
2500RPM	13	21	6	23
3000RPM	23	37	7	26
3500RPM	29	47	9	34
4000RPM	34	55	11	42
4500RPM	40	64	14	53
5000RPM	44	71	19	72
5500RPM	50	81	25	95
WOT	55	89	28	106

Performance and Fuel Flows may vary widely due to Boat Weight, Load, Atmospheric Conditions, Engine Conditions, Weight Distribution, Sea Conditions, Propeller, Boat Bottom Condition, Trim Angle and Operator Technique.



FAST FACTS NOTES

HORIZON 260

Includes RS & SS

SPECIFICATIONS*

	US	METRIC
LOA	26'3"	8.00 m
Beam	8'5"	2.55 m
Fuel Capacity	70 gal	265 L
Draft (drive up)	18"	46 cm
Draft (drive down)	35"	89 cm
Maximum Capacity	2250 lbs	1021 kg
Persons Capacity	13	11
Approx. Boat & Engine Weight	4900 lbs	2220 kg
Trailer Weight	1658 lbs	752 kg
Deadrise	20°	20°
Storage Length on Trailer	26'6"	8.00 m
Bridge Clearance	5'3"	1.60 m
Bridge Clearance RS/SS	5'0"	1.52 m
Bridge Clearance with Arch/Tower	8'6"	2.59 m
Total Height	6'3"	1.91 m
Total Height RS/SS	6'0"	1.83 m
Total Height on Trailer	7'10"	2.39 m
Total Height on Trailer RS/SS	7'7"	2.13 m
Height on Trailer w/Wakeboard Tower Dn	8'10"	2.69 m
Height on Trailer w/Wakeboard Tower Up	10'4"	3.15 m
Potable Water (standard or optional)	12 gal	45 L

POWER RATINGS & WEIGHTS

Engine Type	Propshaft Power		Boat & Engine Weights	
	HP	KW	LBS	KG
MC 6.2L 300/B3	300	224	5200	2360
MC 6.2L 350/B3	350	261	5200	2360
MC 6.2L 350/B3/DTS	350	261	5200	2360
MC 8.2MPI/B3X/DTS	380	283	5400	2450
MC 8.2MPI HO/B3X/DTS	430	321	5400	2450
VP V8-300C/DI/DP	300	224	5100	2310
VP V8-350C/DI/DP	350	261	5100	2310
VP V8-350CE/DI/DP/EVC	350	261	5100	2310
VP V8-350CE/DI/OX/EVC	350	261	5100	2310
VP V8 380CE/DP/EVC	380	283	5200	2360
VP V8 430CE/DP/EVC	430	321	5200	2360

RECOMMENDED ENGINE(S)/EQUIPMENT AVG. WEIGHTS

Model	Eng. Type	Boat	Eng.	Fuel	Access.	Trail Wt.
LBS						
H260	VP V8-350C/DI/DP	4100	1000	420	200	1610
KG						
H260	VP V8-350C/DI/DP	1860	454	190	91	683

PERFORMANCE

Power HP/KW	Propeller (Dia x Pitch)		Type	Top Speed		Cruise Range	
	IN	CM		MPH	KPH	MI	KM
MC 6.2L 300/224/B3	24	61	SST	44-47	71-76	130	210
MC 6.2L 350/261/B3	24	61	SST	47-50	76-81	130	210
MC 6.2L 350/261/B3/DTS	24	61	SST	47-50	76-81	130	210
MC 8.2MPI/B3X/DTS/380/283	26	66	SST	50-53	81-85	130	210
MC 8.2MPIHO/B3X/DTS/430/321	26	66	SST	52-55	84-89	130	210
VP V8-300C/224/DI/DP	FH4	FH4	SST	42-45	68-72	150	240
VP V8-350C/261/DI/DP	FH4	FH4	SST	46-49	74-79	150	240
VP V8-350CE/261/DI/DP/EVC	FH4	FH4	SST	46-49	74-79	150	240
VP V8-350CE/261/DI/OX/EVC	FH4	FH4	SST	46-49	74-79	150	240
VP V8-380CE/283DP/EVC	FH4	FH4	SST	50-53	81-85	140	225
VP V8-430CE/321/DP EVC	FH5	FH5	SST	52-55	84-89	140	225

FUEL FLOW DATA - H260 W/MC 6.2L 300/B3

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	8	13	3	11
2500RPM	10	16	6	23
3000RPM	14	23	11	42
3500RPM	26	42	12	45
4000RPM	30	48	14	53
4500RPM	37	60	18	68
5000RPM	42	68	21	75
WOT	46	74	23	87

FUEL FLOW DATA - H260 W/MC 6.2L 350/B3

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	9	14	4	15
2500RPM	16	26	7	27
3000RPM	24	39	10	38
3500RPM	29	47	12	45
4000RPM	35	56	15	57
4500RPM	42	68	18	70
5000RPM	46	74	22	85
WOT	49	79	26	99

FUEL FLOW DATA - H260 W/MC 6.2L 350/B3/DTS

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	9	14	4	15
2500RPM	16	26	7	27
3000RPM	24	39	10	38
3500RPM	29	47	12	45
4000RPM	35	56	15	57
4500RPM	42	68	18	70
5000RPM	46	74	22	85
WOT	49	79	26	99

**FUEL FLOW DATA - H260 W/MC 8.2MPI/B3X/DTS 380**

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	11	18	8	20
2500RPM	22	35	9	34
3000RPM	34	55	12	45
3500RPM	40	64	16	60
4000RPM	46	74	20	76
4500RPM	50	81	26	98
WOT	52	84	29	110

FUEL FLOW DATA - H260 W/MC 8.2MPI HO/B3X/DTS 430

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	11	18	8	30
2500RPM	22	35	9	34
3000RPM	34	55	12	45
3500RPM	40	64	16	60
4000RPM	46	74	21	79
4500RPM	51	82	27	102
WOT	54	87	32	121

FUEL FLOW DATA - H260 W/VP V8-300C/DI/DP

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	8	13	3	11
2500RPM	10	16	6	23
3000RPM	14	23	7	26
3500RPM	21	33	8	30
4000RPM	24	39	10	38
4500RPM	28	45	12	45
5000RPM	34	54	15	57
5500RPM	40	64	18	68
WOT	44	71	23	87

FUEL FLOW DATA - H260 W/VP V8-350C/DI/DP

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	8	13	3	11
2500RPM	10	16	6	23
3000RPM	15	24	7	26
3500RPM	23	37	8	30
4000RPM	26	42	10	38
4500RPM	30	48	13	49
5000RPM	37	60	17	64
5500RPM	43	69	21	79
WOT	48	77	26	98

**FUEL FLOW DATA - H260 W/VP V8-350CE/DI/DP/EVC**

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	8	13	3	11
2500RPM	10	16	6	23
3000RPM	15	24	7	26
3500RPM	23	37	8	30
4000RPM	26	42	10	38
4500RPM	30	48	13	49
5000RPM	37	60	17	64
5500RPM	43	69	21	79
WOT	48	77	26	98

FUEL FLOW DATA - H260 W/VP V8-350CE/DI/OX/EVC

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	8	13	3	11
2500RPM	10	16	6	23
3000RPM	15	24	7	26
3500RPM	23	37	8	30
4000RPM	26	42	10	38
4500RPM	30	48	13	49
5000RPM	37	60	17	64
5500RPM	43	69	21	79
WOT	48	77	26	98

FUEL FLOW DATA - H260 W/VP V8-380CE/DP/EVC

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	9	14	6	23
2500RPM	14	23	8	30
3000RPM	25	40	10	38
3500RPM	34	55	14	53
4000RPM	39	63	17	64
4500RPM	42	68	20	76
5000RPM	45	72	23	87
5500RPM	48	77	26	98
WOT	51	82	28	106

FUEL FLOW DATA - H260 W/VP V8-430CE/DP/EVC

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	9	14	6	23
2500RPM	14	23	8	30
3000RPM	25	40	10	38
3500RPM	34	55	14	53
4000RPM	39	63	17	64
4500RPM	42	68	21	79
5000RPM	45	72	25	95
5500RPM	49	79	28	106
WOT	53	85	31	117



HORIZON 290

SPECIFICATIONS* US METRIC

LOA	30'1"	9.16 m
Beam	9'5"	2.87 m
Fuel Capacity	120 gal	458 L
Draft (drive up)	25"	64 cm
Draft (drive down)	39"	99 cm
Maximum Capacity	Yacht	1200 kg
Persons Capacity	Yacht	12 (CE)
Approx. Boat & Engine Weight	7200 - 8500 lbs	3266 - 3856 kg
Trailer Weight	N/A	N/A
Deadrise	21°	21°
Bridge Clearance	5'6"	1.68 m
Bridge Clearance with Arch	8'0"	2.44 m
Total Height	7'4"	2.23 m
Potable Water	20 gal	76 L
Holding Tank	6.5 gal	25 L

POWER RATINGS & WEIGHTS

Engine Weights Type	Propshaft Power		Boat & Engine	
	HP	KW	LBS	KG
MC 8.2MPI/B3X/DTS	380	283	7900	3580
MC 8.2MPI HO/B3X/DTS	430	321	7900	3580
TWIN MC 6.2L 300/B3/DTS	600	448	8800	3990
TWIN MC 6.2L 300/B3/DTS/JPS	600	448	8800	3990
TWIN MC 6.2L 350/B3/DTS	700	522	8800	3990
TWIN MC 6.2L 350/B3/DTS/JPS	700	522	8800	3990
VP V8-380/DP/EVC	380	283	7600	3450
VP V8-430/DP/EVC	430	321	7600	3450
TWIN VP V8-300CE/DI/DP/EVC	600	448	8500	3850
TWIN VP V8-300CE/DI/DP/EVC/JOYSTICK	600	448	8500	3850
TWIN VP V8-350CE/DI/DP/EVC	700	522	8500	3850
TWIN VP V8-350CE/DI/DP/EVC/JOYSTICK	700	522	8500	3850
TWIN VP V8-380CE/DP/EVC	760	567	8700	3950
TWIN VP V8-380CE/DP/EVC/JOYSTICK	760	567	8700	3950

RECOMMENDED ENGINE(S)/EQUIPMENT AVG. WEIGHTS

Model	Eng. Type	Boat	Eng.	Fuel	Access.
LBS					
H290	Twin VP V8-350CE/DI/DP	6500	2000	780	300
KG					
H290	Twin VP V8-350CE/DI/DP	2959	910	354	136



PERFORMANCE

Power HP/KW	Propeller (Dia x Pitch)		Type	Top Speed		Cruise Range	
	IN	CM		MPH	KPH	MI	KM
MC 8.2MPI/B3X 380/283/DTS	22.5	56	SST	41-44	66-71	120	190
MC 8.2MPI HO/B3X 430/321/DTS	22.5	56	SST	43-46	69-74	120	190
Twin MC 6.2L 300/224/B3/DTS	24	61	SST	50-53	81-85	130	210
Twin MC 6.2L 300/224/B3/DTS/JPS	24	61	SST	50-53	81-85	130	210
Twin MC 6.2L 350/261/B3/DTS	26	66	SST	54-57	87-92	130	210
Twin MC 6.2L 350/261/B3/DTS/JPS	26	66	SST	54-57	87-92	130	210
VP V8-380CE/283/DP/EVC	FH4	FH4	SST	41-44	66-71	130	210
VP V8-430CE/321/DP/EVC	FH4	FH4	SST	43-46	69-74	130	210
Twin VP V8-300/224DI/DP/EVC	FH5	FH5	SST	50-53	81-85	150	240
Twin VP V8-300/224DI/DP/EVC/JOYSTICK	FH5	FH5	SST	50-53	81-85	150	240
Twin VP V8-350/261/DI/DP	FH6	FH6	SST	54-57	87-92	150	240
Twin VP V8-350/261/DI/DP/JOYSTICK	FH6	FH6	SST	54-57	87-92	150	240
Twin VP V8-380CE/283/DP/EVC	FH6	FH6	SST	57-60	92-97	140	225
Twin VP V8-380CE/283DP/EVC/JOYSTICK	FH6	FH6	SST	57-60	92-97	140	225

FUEL FLOW DATA - H290 W/ MC 8.2MPI/B3X

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	9	14	7	26
2500RPM	11	18	11	42
3000RPM	14	23	15	57
3500RPM	29	47	16	60
4000RPM	34	55	19	72
4500RPM	39	63	27	102
WOT	42	68	32	121

FUEL FLOW DATA - H290 W/ MC 8.2MPI HO/B3X

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	9	14	7	26
2500RPM	11	18	12	45
3000RPM	14	23	15	57
3500RPM	30	48	17	64
4000RPM	35	56	19	72
4500RPM	40	64	28	106
WOT	44	71	35	132

FUEL FLOW DATA - H290 W/TWIN MC 6.2L 300/B3/DTS

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	8	13	9	34
2500RPM	15	24	12	45
3000RPM	25	40	14	53
3500RPM	33	53	17	64
4000RPM	38	61	23	87
4500RPM	43	69	30	113
5000RPM	48	77	39	147
WOT	52	84	46	174

**FUEL FLOW DATA - H290 W/TWIN MC 6.2L 300/B3/DTS/JPS**

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	8	13	9	34
2500RPM	15	24	12	45
3000RPM	25	40	14	53
3500RPM	33	53	17	64
4000RPM	38	61	23	87
4500RPM	43	69	30	113
5000RPM	48	77	39	147
WOT	52	84	46	174

FUEL FLOW DATA - H290 W/TWIN MC 6.2L 350/B3/DTS

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	9	14	8	30
2500RPM	17	27	14	53
3000RPM	27	43	20	76
3500RPM	36	57	25	95
4000RPM	43	69	30	113
4500RPM	48	77	37	140
5000RPM	53	85	45	170
WOT	56	90	52	197

FUEL FLOW DATA - H290 W/TWIN MC 6.2L350/B3/DTS/JPS

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	9	14	8	30
2500RPM	17	27	14	53
3000RPM	27	43	20	76
3500RPM	36	57	25	95
4000RPM	43	69	30	113
4500RPM	48	77	37	140
5000RPM	53	85	45	170
WOT	56	90	52	197

FUEL FLOW DATA - H290 W/VP-V8-380CE/DP/EVC

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	8	13	5	19
2500RPM	10	16	6	23
3000RPM	12	19	7	26
3500RPM	26	42	9	34
4000RPM	30	48	11	48
4500RPM	36	58	14	53
5000RPM	39	63	19	72
5500RPM	41	66	25	95
WOT	42	68	30	113

**FUEL FLOW DATA - H290 W/VP V8-430CE/DP/EVC**

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	8	13	5	19
2500RPM	10	16	6	23
3000RPM	13	21	7	26
3500RPM	26	42	9	34
4000RPM	30	48	11	48
4500RPM	36	58	15	57
5000RPM	39	63	19	72
5500RPM	42	68	26	98
WOT	44	71	33	125

FUEL FLOW DATA - H290 W/ TWIN VP V8-300C/DP

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	10	16	10	38
2500RPM	16	26	15	57
3000RPM	27	43	17	64
3500RPM	33	53	21	79
4000RPM	38	61	28	106
4500RPM	43	69	34	128
5000RPM	47	76	40	151
WOT	50	81	45	170

FUEL FLOW DATA - H290 W/TWIN VP V8-300CE/DI/DP/EVC

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	8	13	6	23
2500RPM	9	14	10	38
3000RPM	13	21	15	57
3500RPM	23	37	16	60
4000RPM	30	48	20	76
4500RPM	37	60	25	95
5000RPM	42	68	33	125
5500RPM	48	77	41	155
WOT	52	84	46	174

FUEL FLOW DATA - H290 W/ TWIN VP V8-300CE/DI/DP/EVC/JOYSTICK

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	8	13	6	23
2500RPM	9	14	10	38
3000RPM	13	21	15	57
3500RPM	23	37	16	60
4000RPM	30	48	20	76
4500RPM	37	60	25	95
5000RPM	42	68	33	125
5500RPM	48	77	41	155
WOT	52	84	46	174

**FUEL FLOW DATA - H290 W/TWIN VP V8-350/DI/DP**

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	8	13	6	23
2500RPM	10	16	11	42
3000RPM	12	19	16	64
3500RPM	18	29	21	83
4000RPM	28	45	23	87
4500RPM	37	60	25	95
5000RPM	44	71	31	117
5500RPM	51	82	43	162
WOT	56	90	52	197

FUEL FLOW DATA - H290 W/ TWIN VP V8-350/DI/300/JOYSTICK

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	8	13	6	23
2500RPM	10	16	11	42
3000RPM	12	19	16	64
3500RPM	18	29	21	83
4000RPM	28	45	23	87
4500RPM	37	60	25	95
5000RPM	44	71	31	117
5500RPM	51	82	43	162
WOT	56	90	52	197

FUEL FLOW DATA - H290 W/ TWIN VP V8-380/DP/380/283 KW

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	10	16	9	34
2500RPM	15	24	13	49
3000RPM	26	42	15	57
3500RPM	33	53	18	68
4000RPM	38	61	22	83
4500RPM	44	71	29	110
5000RPM	49	79	39	147
5500RPM	54	87	51	193
WOT	59	95	60	227

Performance and Fuel Flows may vary widely due to Boat Weight, Load, Atmospheric Conditions, Engine Conditions, Weight Distribution, Sea Conditions, Propeller, Boat Bottom Condition, Trim Angle and Operator Technique.

**FAST FACTS NOTES**



HORIZON 350

SPECIFICATIONS*	US	METRIC
LOA	35'0"	10.7 m
Beam	10'10"	3.30 m
Fuel Capacity	170 gal	644 L
Draft (drive up)	29"	64 cm
Draft (drive down)	41"	104 cm
Maximum Capacity	Yacht	Yacht
Persons Capacity	Yacht	16
Approx. Boat & Engine Weight	12,800 lbs	5,800 kg
Deadrise	19°	19°
Bridge Clearance with Arch	9'0"	2.74 m
Total Height	11'0"	3.35 m
Potable Water (standard or optional)	35 gal	133 L
Holding Tank	25 gal	95 L
Grey Water	25 gal	95 L
Generator	5.0 kw	5.0 kw
Air Conditioning/Heater	12,000 BTU	12,000 BTU
Maximum capacity-swim platform	650 lbs	295 kg

POWER RATINGS & WEIGHTS

Engine Type	Propshaft Power		Boat & Engine Weights	
	HP	KW	LBS	KG
TWIN MC 6.2L 300/B3/DTS	300	224	13000	5900
TWIN MC 6.2L 350/B3/DTS	350	261	13000	5900
TWIN MC 6.2L 350/B3/DTS/JPS	350	261	13000	5900
TWIN MC 6.2L 350/B3/DTS SC	350	261	13000	5900
TWIN MC 8.2MPI/B3/DTS	380	283	13400	6080
TWIN MC 8.2MPI/B3/DTS/JPS	380	283	13400	6080
TWIN MC 8.2MPI/B3/DTS/SC	380	283	13400	6080
TWIN MC 8.2MPI/HO/B3/DTS/JPS	380	283	13400	6080
TWIN MC 8.2MPI/HO/B3/DTS/JPS	430	321	13400	6080
TWIN VP V8-300/DI/DP/EVC	300	224	12600	5710
TWIN VP V8-350/DI/DP/EVC	350	261	12600	5710
TWIN VP V8-350/DI/DP/EVC/JOYSTICK	350	261	12600	5710
TWIN VP V8-380/DP/EVC	380	283	12900	5850
TWIN VP V8-380/OX/EVC	380	283	12900	5850
TWIN VP V8-380/DP/EVC/JOYSTICK	380	283	12900	5850
TWIN VP V8-380/OX/EVC/JOYSTICK	380	283	12900	5850
TWIN VP V8-430/DP/EVC/JOYSTICK	430	321	12900	5850

RECOMMENDED ENGINE(S)/EQUIPMENT AVG. WEIGHTS

Model	Eng. Type	Boat	Eng.	Fuel	Access.
LBS					
H 350	VP V8-380CE/DP/EVC	10700	2200	960	500
KG					
H 350	VP V8-380CE/DP/EVC	4850	1000	435	227



PERFORMANCE

Power HP/KW	Propeller (Dia x Pitch)		Type	Top Speed		Cruise Range	
	IN	CM		MPH	KPH	MI	KM
Twin MC 6.2L 300/224/B3/DTS	24	61	SST	43-46	69-74	160	260
Twin MC 6.2L 350/261/B3/DTS	26	66	SST	46-49	74-79	160	260
Twin MC 6.2L 350/261/B3/DTS/JPS	26	66	SST	46-49	74-79	160	260
Twin MC 6.2L 350/261/B3/DTS SC	26	66	SST	46-49	74-79	160	260
Twin MC 8.2MPI/B3/DTS/380/283	26	66	SST	48-51	77-82	160	260
Twin MC 8.2MPI/B3/DTS/JPS/380/283	26	66	SST	48-51	77-82	160	260
Twin MC 8.2MPI/B3/DTS/SC/380/283	26	66	SST	48-51	77-82	160	260
Twin MC 8.2MPI/B3/DTS/SC/JPS/380/283	26	66	SST	48-51	77-82	160	260
Twin MC 8.2MPI/HO/B3/DTS/JPS/430/321	26	66	SST	50-53	81-85	160	260
Twin VP V8-300CE/224/DI/DP/EVC	FH5	FH5	SST	43-46	69-74	180	290
Twin VP V8-300CE/261/DI/DP/EVC	FH5	FH5	SST	46-49	74-79	180	290
Twin VP V8-350/261/DI/DP/EVC/JOYSTICK	FH5	FH5	SST	46-49	74-79	170	270
Twin VP V8-380/283/DP/EVC	FH5	FH5	SST	46-49	74-79	170	270
Twin VP V8-380/283/OX/EVC	FH5	FH5	SST	48-51	77-82	170	270
Twin VP V8-380/283/DP/EVC/JOYSTICK	FH5	FH5	SST	48-51	77-82	170	270
Twin VP V8-380/283/OX/JOYSTICK	FH5	FH5	SST	48-51	77-82	170	270
Twin VP V8-430/321/DP/JOYSTICK	FH5	FH5	SST	50-53	81-85	170	270

FUEL FLOW DATA - H350 W/TWIN MC 6.2L 300/B3/DTS

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	8	13	9	34
2500RPM	14	23	12	45
3000RPM	23	37	14	53
3500RPM	30	48	17	64
4000RPM	34	55	23	87
4500RPM	38	61	30	113
5000RPM	42	68	39	147
WOT	45	72	46	174

FUEL FLOW DATA - H350 W/TWIN MC 6.2L 350/B3/DTS

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	8	13	9	34
2500RPM	14	23	12	45
3000RPM	23	37	17	64
3500RPM	30	48	24	91
4000RPM	34	55	30	113
4500RPM	39	63	37	140
5000RPM	44	71	45	170
WOT	48	77	52	197

**FUEL FLOW DATA - H350 W/TWIN MC 6.2L 350/B3/DTS/SC**

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	8	13	9	34
2500RPM	14	23	12	45
3000RPM	23	37	17	64
3500RPM	30	48	24	91
4000RPM	34	55	30	113
4500RPM	39	63	37	140
5000RPM	44	71	45	170
WOT	48	77	52	197

FUEL FLOW DATA - H350 W/TWIN MC 6.2L 350/B3/DTS/JPS

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	8	13	9	34
2500RPM	14	23	12	45
3000RPM	23	37	17	64
3500RPM	30	48	24	91
4000RPM	34	55	30	113
4500RPM	39	63	37	140
5000RPM	44	71	45	170
WOT	48	77	52	197

FUEL FLOW DATA - H350 W/TWIN MC 8.2MPI/B3X/DTS/380

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	10	16	16	60
2500RPM	13	21	23	87
3000RPM	29	47	26	98
3500RPM	37	60	34	129
4000RPM	42	68	43	162
4500RPM	48	77	54	204
WOT	50	81	62	234

FUEL FLOW DATA - H350 W/TWIN MC 8.2MPI/B3X/DTS/JPS/380

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	10	16	16	60
2500RPM	13	21	23	87
3000RPM	29	47	26	98
3500RPM	37	60	34	129
4000RPM	42	68	43	162
4500RPM	48	77	54	204
WOT	50	81	62	234

**FUEL FLOW DATA - H350 W/TWIN MC 8.2MPI/B3X/DTS/SC/380**

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	10	16	16	60
2500RPM	13	21	23	87
3000RPM	29	47	26	98
3500RPM	37	60	34	129
4000RPM	42	68	43	162
4500RPM	48	77	54	204
WOT	50	81	62	234

FUEL FLOW DATA - H350 W/TWIN MC 8.2MPI/B3X/DTS/SC/JPS/380

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	10	16	16	60
2500RPM	13	21	23	87
3000RPM	29	47	26	98
3500RPM	37	60	34	129
4000RPM	42	68	43	162
4500RPM	48	77	54	204
WOT	50	81	62	234

FUEL FLOW DATA - H350 W/TWIN MC 8.2MPI/HO/B3X/DTS/JPS/430

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	10	16	16	60
2500RPM	13	21	23	87
3000RPM	29	47	26	98
3500RPM	37	60	34	129
4000RPM	42	68	43	162
4500RPM	48	77	58	219
WOT	51	83	72	272

FUEL FLOW DATA - H350 W/TWIN VP V8-300CE/DI/DP/EVC

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	8	13	6	23
2500RPM	9	14	10	38
3000RPM	13	21	15	57
3500RPM	23	37	16	60
4000RPM	29	47	20	76
4500RPM	35	56	25	95
5000RPM	38	52	33	125
5500RPM	42	68	41	155
WOT	45	72	46	174

**FUEL FLOW DATA - H350 W/TWIN VP V8-350CE/DI/DP/EVC**

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	8	13	6	23
2500RPM	10	16	11	42
3000RPM	11	18	16	64
3500RPM	16	26	21	83
4000RPM	25	40	23	87
4500RPM	32	52	25	95
5000RPM	38	61	31	117
5500RPM	43	69	43	162
WOT	48	77	52	197

FUEL FLOW DATA - H350 W/TWIN VP V8-350CE/DI/DP/EVC/JSTK

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	8	13	6	23
2500RPM	10	16	11	42
3000RPM	11	18	16	64
3500RPM	16	26	21	83
4000RPM	25	40	23	87
4500RPM	32	52	25	95
5000RPM	38	61	31	117
5500RPM	43	69	43	162
WOT	48	77	52	197

FUEL FLOW DATA - H350 W/TWIN VP V8-380CE/DP/EVC

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	9	14	8	30
2500RPM	11	18	14	53
3000RPM	16	26	19	72
3500RPM	26	42	22	83
4000RPM	33	53	27	102
4500RPM	38	61	32	121
5000RPM	43	69	43	163
5500RPM	48	77	54	204
WOT	50	81	61	231

FUEL FLOW DATA - H350 W/TWIN VP V8-380CE/OX/EVC

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	9	14	8	30
2500RPM	11	18	14	53
3000RPM	16	26	19	72
3500RPM	26	42	22	83
4000RPM	33	53	27	102
4500RPM	38	61	32	121
5000RPM	43	69	43	163
5500RPM	48	77	54	204
WOT	50	81	61	231

**FUEL FLOW DATA - H350 W/TWIN VP V8-380CE/DP/EVC/JOYSTICK**

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	9	14	8	30
2500RPM	11	18	14	53
3000RPM	16	26	19	72
3500RPM	26	42	22	83
4000RPM	33	53	27	102
4500RPM	38	61	32	121
5000RPM	43	69	43	163
5500RPM	48	77	54	204
WOT	50	81	61	231

FUEL FLOW DATA - H350 W/TWIN VP V8-380CE/OX/EVC/JOYSTICK

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	9	14	8	30
2500RPM	11	18	14	53
3000RPM	16	26	19	72
3500RPM	26	42	22	83
4000RPM	33	53	27	102
4500RPM	38	61	32	121
5000RPM	43	69	43	163
5500RPM	48	77	54	204
WOT	50	81	61	231

FUEL FLOW DATA - H350 W/TWIN VP V8-430CE/DP/EVC/JOYSTICK

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	9	14	8	30
2500RPM	11	18	14	53
3000RPM	16	26	19	72
3500RPM	26	42	22	83
4000RPM	33	53	27	102
4500RPM	38	61	32	121
5000RPM	43	69	43	163
5500RPM	49	79	56	212
WOT	52	84	66	249

Performance and Fuel Flows may vary widely due to Boat Weight, Load, Atmospheric Conditions, Engine Conditions, Weight Distribution, Sea Conditions, Propeller, Boat Bottom Condition, Trim Angle and Operator Technique.



TS SERIES



TS 222

SPECIFICATIONS* US METRIC

LOA	22'7"	6.88 m
Beam	8'6"	2.59 m
Fuel Capacity	44 gal	166 L
Draft (drive up)	17"	43 cm
Draft (drive down)	33"	84 cm
Maximum Capacity	1800 lbs	816 kg
Persons Capacity	12	8
Approx. Boat & Engine Weight	4240 lbs	1920 kg
Trailer Weight	1256 lbs	570 kg
Deadrise	20°	20°
Storage Length on Trailer	23'5"	7.14 m
Bridge Clearance with Arch/Tower	6'8"	2.09 m
Total Height	5'8"	1.73 m
Total Height on Trailer	7'5"	2.26 m
Height on Trailer w/Wakeboard Tower Dn	9'1"	2.77 m
Height on Trailer w/Wakeboard Tower Up	10'5"	3.23 m
Potable Water (standard or optional)	12 gal	45 L
Ballast	1300 lbs	590 kg

POWER RATINGS & WEIGHTS

Engine Type	Propshaft Power		Boat & Engine Weights	
	HP	KW	LBS	KG
VP V8-300/DI/FWD	300	224	4160	1890
VP V8-350/DI/FWD	350	261	4160	1890

RECOMMENDED ENGINE(S)/EQUIPMENT AVG. WEIGHTS

Model	Eng. Type	Boat	Eng.	Fuel	Access.
-------	-----------	------	------	------	---------

LBS

TS 222	V8-300/DI/FWD	3160	1000	300	150
--------	---------------	------	------	-----	-----

KG

TS 222	V8-300/DI/FWD	1430	454	136	68
--------	---------------	------	-----	-----	----

PERFORMANCE

Power HP/KW	Propeller (Dia x Pitch)		Type	Top Speed		Cruise Range	
	IN	CM		MPH	KPH	MI	KM
VP V8-300/DI/FWD	K3	K3	SST	40-45	64-72	135	217
VP V8-350/DI/FWD	K4	K4	SST	44-50	71-81	135	217



FUEL FLOW DATA - TS222 W/VP V8-300/DI/FWD

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	8	13	3	11
2500RPM	9	14	5	19
3000RPM	13	21	7	26
3500RPM	22	35	8	30
4000RPM	29	47	10	38
4500RPM	33	53	13	49
5000RPM	37	60	16	60
5500RPM	40	64	21	79
WOT	43	69	23	87

FUEL FLOW DATA - TS222 W/VP V8-350/DI/FWD

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	8	13	4	15
2500RPM	10	16	6	23
3000RPM	17	27	7	26
3500RPM	26	42	8	30
4000RPM	32	52	11	42
4500RPM	36	58	14	53
5000RPM	40	64	20	76
4500RPM	44	71	23	87
WOT	47	76	26	98

Performance and Fuel Flows may vary widely due to Boat Weight, Load, Atmospheric Conditions, Engine Conditions, Weight Distribution, Sea Conditions, Propeller, Boat Bottom Condition, Trim Angle and Operator Technique.



TS 242

SPECIFICATIONS*	US	METRIC
LOA	24'5"	7.44 m
Beam	8'6"	2.59 m
Fuel Capacity	55 gal	208 L
Draft (drive up)	17"	43 cm
Draft (drive down)	33"	84 cm
Maximum Capacity	2100 lbs	953 kg
Persons Capacity	14	10
Approx. Boat & Engine Weight	4660 lbs	2110 kg
Trailer Weight	1418 lbs	643 kg
Deadrise	20°	20°
Storage Length on Trailer	24'5"	7.44 m
Bridge Clearance with Arch/Tower	7'3"	2.21 m
Total Height	6'4"	1.93 m
Total Height on Trailer	7'9"	2.36 m
Height on Trailer w/Wakeboard Tower Dn	9'5"	2.87 m
Height on Trailer w/Wakeboard Tower Up	10'9"	3.28 m
Potable Water (standard or optional)	15 gal	57 L
Ballast	1800 lbs	816 kg

POWER RATINGS & WEIGHTS

Engine Type	Propshaft Power		Boat & Engine Weights	
	HP	KW	LBS	KG
VP V8-300C/DI/FWD	300	224	4630	2100
VP V8-350C/DI/FWD	350	261	4630	2100
VP V8-380C/FWD	380	283	4710	2140

RECOMMENDED ENGINE(S)/EQUIPMENT AVG. WEIGHTS

Model	Eng. Type	Boat	Eng.	Fuel	Access.
LBS					
TS 242	V8-350C/DI/FWD	3630	1000	330	200
KG					
TS 242	V8-350C/DI/FWD	1650	454	150	91

PERFORMANCE

Power HP/KW	Propeller (Dia x Pitch)		Type	Top Speed		Cruise Range	
	IN	CM		MPH	KPH	MI	KM
VP V8-300C/224/DI/FWD	K3 TOW	K3	SST	40-43	64-69	130	209
VP V8-350C/261/DI/FWD	K3 TOW	K3	SST	41-44	66-74	130	209
VP V8-380C/283/FWD	K4 TOW	K4	SST	44-46	71-79	120	193



FUEL FLOW DATA - TS242 W/VP V8-300C/DI/FWD

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	8	13	3	11
2500RPM	9	14	5	19
3000RPM	13	21	7	26
3500RPM	22	35	8	30
4000RPM	29	47	10	38
4500RPM	33	53	13	49
5000RPM	36	58	16	60
5500RPM	39	63	21	79
WOT	42	68	23	87

FUEL FLOW DATA - TS242 W/VP V8-350C/DI/FWD

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	8	13	3	11
2500RPM	9	14	5	19
3000RPM	13	21	7	26
3500RPM	22	35	8	30
4000RPM	29	47	10	38
4500RPM	33	53	13	49
5000RPM	37	60	17	64
5500RPM	40	64	23	87
WOT	43	69	27	102

FUEL FLOW DATA - TS242 W/VP V8-380C/FWD

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	9	14	4	15
2500RPM	11	18	7	26
3000RPM	15	24	8	30
3500RPM	22	35	10	38
4000RPM	30	48	12	45
4500RPM	35	56	15	57
5000RPM	39	63	20	76
5500RPM	43	69	26	98
WOT	45	72	29	110

Performance and Fuel Flows may vary widely due to Boat Weight, Load, Atmospheric Conditions, Engine Conditions, Weight Distribution, Sea Conditions, Propeller, Boat Bottom Condition, Trim Angle and Operator Technique.



HD SERIES



HD 220

Includes RS & SS

SPECIFICATIONS*

	US	METRIC
LOA	22'1"	6.73 m
Beam	8'5"	2.57 m
Fuel Capacity	44 gal	166 l
Draft (drive up)	17"	43 cm
Draft (drive down)	33"	53 cm
Maximum Capacity	1800 lbs	816 kg
Persons Capacity	10	9 CE
Approx. Boat & Engine Weight	4170 lbs	1890 kg
Deadrise	20°	20°
Storage Length on Trailer	23'2"	7.06 m
Bridge Clearance	4'9"	1.45 m
Bridge Clearance RS/SS	4'4"	1.32 m
Bridge Clearance with Arch/Tower	7'7"	2.31 m
Total Height	6'2"	1.88 m
Total Height RS/SS	5'9"	1.75 m
Total Height on Trailer	7'10"	2.39 m
Total Height on Trailer RS/SS	7'5"	2.26 m
Height on Trailer w/Wakeboard Tower Dn	9'3"	2.97 m
Height on Trailer w/Wakeboard Tower Up	10'8"	3.25 m
Potable Water	12 gal	45 l

POWER RATINGS & WEIGHTS

Engine Type	Propshaft Power		Boat & Engine Weights	
	HP	KW	LBS	KG
MC 6.2L 300/B1	300	224	4230	1920
MC 6.2L 300/B3	300	224	4230	1920
MC 6.2L 350/B3	300	224	4230	1920
VP V8-300C/DI/SX	300	224	4100	1860
VP V8-300C/DI/DP	300	224	4100	1860
VP V8-350C/DI/DP	300	224	4100	1860

RECOMMENDED ENGINE(S)/EQUIPMENT AVG. WEIGHTS

Model	Eng. Type	Boat	Eng.	Fuel	Access.
LBS					
HD220	VP V8-300C/DI/DP	3100	1000	264	200
KG					
HD220	VP V8-300C/DI/DP	1410	454	120	91



PERFORMANCE

Power HP/KW	Propeller (Dia x Pitch)		Type	Top Speed		Cruise Range	
	IN	CM		MPH	KPH	MI	KM
MC 6.2L 300/B1	15 1/2 x 17	39 X 43	SST	48-51	77-82	120	190
MC 6.2L 300/B3	26	66	SST	49-52	79-84	130	210
MC 6.2L 350/B3	26	66	SST	53-56	85-90	130	210
VP V8-300C/DI/SX	14 3/4 x 17	37 X43	SST	48-51	77-82	130	210
VP V8-300C/DI/DP	FH5	FH5	SST	49-52	79-84	140	225
VP V8-350C/DI/DP	FH6	FH6	SST	53-56	85-90	140	225

FUEL FLOW DATA - HD220 W/MC 6.2L 300/B1

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	8	13	3	11
2500RPM	10	16	6	23
3000RPM	14	23	11	42
3500RPM	27	44	12	45
4000RPM	32	52	14	53
4500RPM	40	64	18	68
5000RPM	46	74	21	75
WOT	50	81	23	87

FUEL FLOW DATA - HD220 W/MC 6.2L 300/B3

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	8	13	3	11
2500RPM	10	16	6	23
3000RPM	14	23	11	42
3500RPM	27	43	12	45
4000RPM	33	53	14	53
4500RPM	41	68	18	68
5000RPM	47	76	21	75
WOT	51	82	23	87

FUEL FLOW DATA - HD220 W/MC 6.2L 350/B3

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	9	14	5	19
2500RPM	19	31	6	23
3000RPM	27	43	8	30
3500RPM	33	53	10	38
4000RPM	40	64	13	49
4500RPM	45	72	18	68
5000RPM	52	84	23	87
WOT	55	89	27	102



HD 220 OB

Includes RS & SS

SPECIFICATIONS*

	US	METRIC
LOA	22'1"	6.73 m
Beam	8'5"	2.57 m
Fuel Capacity	44 gal	166 l
Draft (drive up)	21"	53 cm
Draft (drive down)	35"	89 cm
Maximum Capacity	2650 lbs	1200 kg
Persons Capacity	10	9 CE
Approx. Boat Weight	3530 lbs	1600 kg
Deadrise	20°	20°
Storage Length on Trailer	24'8"	7.52 m
Bridge Clearance	4'11"	1.50 m
Bridge Clearance RS/SS	4'6"	1.37 m
Bridge Clearance with Arch/Tower	7'9"	2.36 m
Total Height	6'2"	1.88 m
Total Height RS/SS	5'9"	1.75 m
Total Height on Trailer	7'10"	2.39 m
Total Height on Trailer RS/SS	7'5"	2.26 m
Height on Trailer w/Wakeboard Tower Dn	9'3"	2.82 m
Height on Trailer w/Wakeboard Tower Up	10'8"	3.25 m
Potable Water	12 gal	45 l

POWER RATINGS & WEIGHTS

Engine Type	Propshaft Power		Boat & Engine Weights	
	HP	KW	LBS	KG
EVINRUDE C200 FX G2	200	149	4040	1830
EVINRUDE E250 X G2	250	187	4090	1850
MERCURY 200XL VERADO	200	149	4050	1840
MERCURY 250XL VERADO	250	187	4190	1900
YAMAHA F200 XB	200	149	4020	1820
YAMAHA F200 XCA	200	149	4020	1820
YAMAHA F250 XB	250	187	4090	1850
YAMAHA F250 XCA	250	187	4090	1850

RECOMMENDED ENGINE(S)/EQUIPMENT AVG. WEIGHTS

Model	Eng. Type	Boat	Eng.	Fuel	Access.
LBS					
HD220 OB	MERC 250XL VERADO	3530	660	264	200
KG					
HD220 OB	MERC 250XL VERADO	1600	299	120	91



PERFORMANCE

Power HP/KW	Propeller (Dia x Pitch)		Type	Top Speed		Cruise Range	
	IN	CM		MPH	KPH	MI	KM
EVINRUDE C200F X G2	15.5 X 17	39 X 43	SST	43-46	69-74	125	200
EVINRUDE E250 X G2	15.5 X 17	39 X 43	SST	48-51	77-82	120	190
MERCURY 200XL VERADO	15 3/4 X 15	40 X 38	SST	43-46	69-74	125	200
MERCURY 250XL VERADO	15 1/2 X 17	39 X 43	SST	48-51	77-82	120	190
YAMAHA F200 XB	14 1/2 X 15	37 X 38	SST	42-45	68-72	115	185
YAMAHA F200 XCA	14 1/2 X 15	37 X 38	SST	42-45	68-72	115	185
YAMAHA F250 XB	15 1/2 X 17	39 X 43	SST	48-51	77-82	120	190
YAMAHA F250 XCA	15 1/2 X 17	39 X 43	SST	48-51	77-82	120	190

FUEL FLOW DATA - HD220 OB-C200FX G2

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	7	11	3	11
2500RPM	8	13	4	15
3000RPM	9	14	6	23
3500RPM	22	35	8	30
4000RPM	30	48	9	34
4500RPM	35	56	10	38
5000RPM	39	63	12	45
5500RPM	43	69	15	57
WOT	45	72	17	64

FUEL FLOW DATA - HD220 OB-E250X G2

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	8	13	3	11
2500RPM	9	14	5	19
3000RPM	10	16	7	26
3500RPM	25	40	8	30
4000RPM	33	53	10	38
4500RPM	37	60	12	45
5000RPM	42	68	15	57
5500RPM	48	77	17	64
WOT	50	81	20	76

FUEL FLOW DATA - HD220 OB-200XL VERADO

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	7	11	3	11
2500RPM	8	13	5	19
3000RPM	9	14	6	23
3500RPM	10	16	8	30
4000RPM	26	42	8	30
4500RPM	31	50	9	34
5000RPM	36	58	10	38
5500RPM	40	64	12	45
6000RPM	43	69	16	60
WOT	45	72	18	68



FUEL FLOW DATA - HD220 OB-250XL VERADO

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	7	11	3	11
2500RPM	8	13	4	15
3000RPM	8	13	7	26
3500RPM	9	14	10	38
4000RPM	28	45	10	38
4500RPM	35	56	12	45
5000RPM	39	63	16	60
5500RPM	44	71	18	68
6000RPM	48	77	21	79
WOT	51	82	23	87

FUEL FLOW DATA - HD220 OB-F200 XCA & XB

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	7	11	3	11
2500RPM	8	13	4	15
3000RPM	9	14	7	26
3500RPM	22	35	8	30
4000RPM	29	47	9	34
4500RPM	35	56	10	38
5000RPM	39	63	13	49
5500RPM	42	69	15	57
WOT	44	71	17	64

FUEL FLOW DATA - HD220 OB-F250XB OR XCA

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	8	13	3	11
2500RPM	9	14	5	19
3000RPM	11	18	7	26
3500RPM	25	40	9	34
4000RPM	33	53	10	38
4500RPM	37	60	13	49
5000RPM	42	68	15	57
5500RPM	47	76	17	64
WOT	50	81	21	79

Performance and Fuel Flows may vary widely due to Boat Weight, Load, Atmospheric Conditions, Engine Conditions, Weight Distribution, Sea Conditions, Propeller, Boat Bottom Condition, Trim Angle and Operator Technique



FAST FACTS NOTES



HD 240

Includes RS & SS

SPECIFICATIONS*

	US	METRIC
LOA	24'5"	7.44 m
Beam	8'5"	2.55 m
Fuel Capacity	55 gal	208 l
Draft (drive up)	18"	46 cm
Draft (drive down)	35"	89 cm
Maximum Capacity	2000 lbs	907 kg
Persons Capacity	11	10 CE
Approx. Boat & Engine Weight	4860 lbs	2200 kg
Deadrise	20°	20°
Storage Length on Trailer	24'10"	7.57 m
Bridge Clearance	4'8"	1.42 m
Bridge Clearance RS/SS	4'3"	1.30 m
Bridge Clearance with Arch/Tower	7'7"	2.31 m
Total Height	6'4"	1.93 m
Total Height RS/SS	5'11"	1.80 m
Total Height on Trailer	8'1"	2.46 m
Total Height on Trailer RS/SS	7'8"	2.34 m
Height on Trailer w/Wakeboard Tower Dn	9'6"	2.90 m
Height on Trailer w/Wakeboard Tower Up	10'11"	3.33 m
Potable Water	12 gal	45 l

POWER RATINGS & WEIGHTS

Engine Type	Propshaft Power		Boat & Engine Weights	
	HP	KW	LBS	KG
MC 6.2L 300/B3	300	224	4960	2250
MC 6.2L 350/B3	350	261	4960	2250
MC 6.2L 350/B3/DTS	350	361	4960	2250
VP V8-300C/DI/DP	300	224	4760	2160
VP V8-350C/DI/DP	350	261	4760	2160
VP V8-350CE/DI/DP/EVC	350	261	4760	2160

RECOMMENDED ENGINE(S)/EQUIPMENT AVG. WEIGHTS

Model	Eng. Type	Boat	Eng.	Fuel	Access.
LBS					
HD240	VP V8-350CE/DI/DP/EVC	3760	1000	324	200
KG					
HD240	VP V8-350CE/DI/DP/EVC	1710	454	147	91



PERFORMANCE

Power HP/KW	Propeller (Dia x Pitch)		Type	Top Speed		Cruise Range	
	IN	CM		MPH	KPH	MI	KM
MC 6.2L 300/B3	24	61		45-48	72-77	140	225
MC 6.2L 350/B3	26	66		49-52	79-84	140	225
MC 6.2L 350/B3/DTS	26	66		49-52	79-84	140	225
VP V8-300C/DI/DP	FH4	FH4		45-48	72-77	150	240
VP V8-350C/DI/DP	FH5	FH5		49-52	79-84	150	240
VP V8-350CE/DI/DP/EVC	FH5	FH5		49-52	79-84	150	240

FUEL FLOW DATA - HD240 -MC 6.2L 300/B3

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	9	14	4	15
2500RPM	10	16	6	23
3000RPM	18	29	8	30
3500RPM	26	42	9	34
4000RPM	32	52	12	45
4500RPM	37	60	15	57
5000RPM	42	68	19	72
WOT	46	74	23	87

FUEL FLOW DATA - HD240 -MC 6.2L 350/B3

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	9	14	4	15
2500RPM	10	16	6	23
3000RPM	18	29	8	30
3500RPM	26	42	9	34
4000RPM	33	53	13	49
4500RPM	39	63	17	64
5000RPM	45	72	22	83
WOT	50	81	27	102

FUEL FLOW DATA - HD240 -MC 6.2L 350/B3/DTS

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	9	14	4	15
2500RPM	10	16	6	23
3000RPM	18	29	8	30
3500RPM	26	42	9	34
4000RPM	33	53	13	49
4500RPM	39	63	17	64
5000RPM	45	72	22	83
WOT	50	81	27	102



FUEL FLOW DATA - HD240 -VP V8-300C/DI/DP

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	9	14	4	15
2500RPM	13	21	6	23
3000RPM	22	35	7	26
3500RPM	28	45	9	34
4000RPM	34	55	11	42
4500RPM	39	63	14	53
5000RPM	45	72	18	68
5500RPM	50	81	24	91
WOT	53	85	28	106

FUEL FLOW DATA - HD240 -VP V8-350C/DI/DP

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	9	14	4	15
2500RPM	13	21	6	23
3000RPM	22	35	7	26
3500RPM	28	45	9	34
4000RPM	34	55	11	42
4500RPM	39	63	14	53
5000RPM	45	72	18	68
5500RPM	50	81	24	91
WOT	53	85	28	106

FUEL FLOW DATA - HD240 -VP V8-350CE/DI/DP/EVC

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	9	14	4	15
2500RPM	13	21	6	23
3000RPM	22	35	7	26
3500RPM	28	45	9	34
4000RPM	34	55	11	42
4500RPM	39	63	14	53
5000RPM	45	72	18	68
5500RPM	50	81	24	91
WOT	53	85	28	106

Performance and Fuel Flows may vary widely due to Boat Weight, Load, Atmospheric Conditions, Engine Conditions, Weight Distribution, Sea Conditions, Propeller, Boat Bottom Condition, Trim Angle and Operator Technique



FAST FACTS NOTES



HD 240 OB

Includes RS & SS

SPECIFICATIONS*

	US	METRIC
LOA	24'4"	7.41 m
Beam	8'5"	2.55 m
Fuel Capacity	55 gal	208 l
Draft (drive up)	18"	46 cm
Draft (drive down)	35"	89 cm
Maximum Capacity	2800 lbs	1270 kg
Persons Capacity	11	12 CE
Approx. Boat & Engine Weight	3940 lbs	1790 kg
Deadrise	20°	20°
Storage Length on Trailer	26'11"	8.21 m
Bridge Clearance	4'7"	1.40 m
Bridge Clearance RS/SS	4'2"	1.27 m
Bridge Clearance with Arch/Tower	7'6"	2.29 m
Total Height	6'4"	1.93 m
Total Height RS/SS	5'11"	1.80 m
Total Height on Trailer	8'1"	2.46 m
Total Height on Trailer RS/SS	7'8"	2.34 m
Height on Trailer w/Wakeboard Tower Dn	9'6"	2.90 m
Height on Trailer w/Wakeboard Tower Up	10'11"	3.33 m
Potable Water	12 gal	45 l

POWER RATINGS & WEIGHTS

Engine Type	Propshaft Power		Boat & Engine Weights	
	HP	KW	LBS	KG
EVINRUDE C200FX G2	200	149	4410	2000
EVINRUDE E250 X G2	250	187	4500	2040
EVINRUDE E300 XU G2	300	224	4510	2050
MERCURY 200XL VERADO	200	149	4460	2020
MERCURY 250XL VERADO	250	187	4600	2090
MERCURY 300XL VERADO	300	224	4600	2090
YAMAHA F200 XB	200	149	4430	2010
YAMAHA F200 XCA	200	149	4430	2010
YAMAHA F250 XB	250	187	4500	2040
YAMAHA F250 XCA	250	187	4500	2040
YAMAHA F300 XCA	300	224	4500	2040

RECOMMENDED ENGINE(S)/EQUIPMENT AVG. WEIGHTS

Model	Eng. Type	Boat	Eng.	Fuel	Access.
LBS					
HD240 OB	MERC 250XL VERADO	3940	660	324	200
KG					
HD240 OB	MERC 250XL VERADO	1790	299	147	91



PERFORMANCE

Power HP/KW	Propeller (Dia x Pitch)		Type	Top Speed		Cruise Range	
	IN	CM		MPH	KPH	MI	KM
EVINRUDE C200 FX G2	15 1/2 X 17	39 X 43	SST	42-45	66-71	110	180
EVINRUDE E250 X G2	15 1/2 X 17	39 X 43	SST	46-49	74-79	100	160
EVINRUDE E300 XU G2	15 X 18	38 X 46	SST	49-52	79-84	100	160
MERCURY 200XL VERADO	15 3/4 X 15	40 X 38	SST	41-44	66-71	110	180
MERCURY 250XL VERADO	15 1/2 X 17	39 X 43	SST	46-49	74-79	100	160
MERCURY 300XL VERADO	15 3/8 X 19	39 X 48	SST	49-52	79-84	100	160
YAMAHA F200 XB	14 1/2 X 15	37 X 38	SST	41-44	66-71	100	160
YAMAHA F200 XCA	14 1/2 X 15	37 X 38	SST	41-44	66-71	100	160
YAMAHA F250 XB	15 1/2 X 17	39 X 43	SST	46-49	74-79	110	180
YAMAHA F250 XCA	15 1/2 X 17	39 X 43	SST	46-49	74-79	110	180
YAMAHA F300 XCA	15 1/4 X 19	39 X 48	SST	49-52	79-84	100	160

FUEL FLOW DATA - HD240 OB-C200FX G2

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	7	11	2	8
2500RPM	8	13	4	15
3000RPM	9	14	6	23
3500RPM	11	18	8	30
4000RPM	25	40	9	34
4500RPM	32	52	10	38
5000RPM	36	58	11	42
5500RPM	40	64	14	53
WOT	43	69	16	60

FUEL FLOW DATA - HD240 OB-E250X G2

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	8	13	3	11
2500RPM	9	14	5	19
3000RPM	10	16	7	26
3500RPM	12	19	9	34
4000RPM	27	43	10	38
4500RPM	34	55	12	45
5000RPM	40	64	14	53
5500RPM	44	71	17	64
WOT	48	77	20	76

Performance and Fuel Flows may vary widely due to Boat Weight, Load, Atmospheric Conditions, Engine Conditions, Weight Distribution, Sea Conditions, Propeller, Boat Bottom Condition, Trim Angle and Operator Technique



FUEL FLOW DATA - HD240 OB-E300XU G2

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	8	13	3	11
2500RPM	9	14	5	19
3000RPM	10	16	7	26
3500RPM	13	21	9	34
4000RPM	27	43	10	38
4500RPM	36	58	13	49
5000RPM	41	66	15	57
5500RPM	45	72	18	68
WOT	50	81	24	91

FUEL FLOW DATA - HD240 OB-200XL VERADO

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	7	11	2	8
2500RPM	8	13	4	15
3000RPM	9	14	6	23
3500RPM	10	16	7	26
4000RPM	24	39	8	30
4500RPM	29	47	9	34
5000RPM	32	52	10	38
5500RPM	37	60	13	49
6000RPM	40	64	14	53
WOT	43	69	16	60

FUEL FLOW DATA - HD240 OB-250XL VERADO

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	7	11	3	11
2500RPM	8	13	5	19
3000RPM	9	14	6	23
3500RPM	10	16	8	30
4000RPM	25	40	9	34
4500RPM	31	50	11	42
5000RPM	35	56	13	49
5500RPM	40	64	16	60
6000RPM	44	71	18	68
WOT	48	77	20	76



FUEL FLOW DATA - HD240 OB-300XL VERADO

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	7	11	3	11
2500RPM	8	13	5	19
3000RPM	10	16	6	23
3500RPM	11	18	8	30
4000RPM	27	43	10	38
4500RPM	33	53	13	49
5000RPM	37	60	15	57
5500RPM	41	66	19	72
6000RPM	47	76	21	79
WOT	50	81	24	91

FUEL FLOW DATA - HD240 OB-F200XCA & XB

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	7	11	2	8
2500RPM	8	13	4	15
3000RPM	9	14	6	23
3500RPM	11	18	8	30
4000RPM	25	40	9	34
4500RPM	32	52	10	38
5000RPM	37	60	12	45
5500RPM	40	64	14	53
WOT	43	69	16	60

FUEL FLOW DATA - HD240 OB-F250XCA

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	8	13	3	11
2500RPM	9	14	5	19
3000RPM	10	16	7	26
3500RPM	13	21	9	34
4000RPM	28	45	11	42
4500RPM	37	60	13	49
5000RPM	41	66	15	57
5500RPM	44	71	17	64
WOT	48	77	20	76

FUEL FLOW DATA - HD240 OB-F300XCA

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	8	13	3	11
2500RPM	9	14	5	19
3000RPM	10	16	7	26
3500RPM	14	23	9	34
4000RPM	29	47	11	42
4500RPM	37	60	14	53
5000RPM	43	69	16	60
5500RPM	47	76	18	68
WOT	50	81	24	91



HD 270

Includes RS & SS

SPECIFICATIONS*

	US	METRIC
LOA	26'6"	8.08 m
Beam	8'5"	2.57 m
Fuel Capacity	70 gal	265 l
Draft (drive up)	17"	43 cm
Draft (drive down)	33"	53 cm
Maximum Capacity	Yacht	Yacht
Persons Capacity	Yacht	12 CE
Approx. Boat & Engine Weight	5350 lbs	2430 kg
Deadrise	20°	20°
Storage Length on Trailer	26'6"	8.08 m
Bridge Clearance	4'8"	1.42 m
Bridge Clearance RS/SS	4'3"	1.30 m
Bridge Clearance with Arch/Tower	7'7"	2.31 m
Total Height	6'5"	1.96 m
Total Height RS/SS	6'0"	1.83 m
Total Height on Trailer	8'3"	2.52 m
Total Height on Trailer RS/SS	7'10"	2.39 m
Height on Trailer w/Wakeboard Tower Dn	9'9"	2.97 m
Height on Trailer w/Wakeboard Tower Up	11'3"	3.43 m
Potable Water	12 gal	45 l

POWER RATINGS & WEIGHTS

Engine Type	Propshaft Power		Boat & Engine Weights	
	HP	KW	LBS	KG
MC 6.2L 300/B3	300	224	5400	2450
MC 6.2L 350/B3	350	261	5400	2450
MC 6.2L 350/B3/DTS	350	261	5400	2450
MC 6.2L 350/B3/SC/DTS	350	261	5400	2450
MC 8.2MPI/B3X/DTS	380	283	5600	2540
VP V8-300C/DI/DP	300	224	5200	2360
VP V8-350C/DI/DP	350	261	5200	2360
VP V8-350CE/DI/DP/EVC	350	261	5200	2360
VP V8-350CE/DI/OX/EVC	350	261	5200	2360
VP V8 380CE/DI/DP/EVC	380	283	5300	2400

RECOMMENDED ENGINE(S)/EQUIPMENT AVG. WEIGHTS

Model	Eng. Type	Boat	Eng.	Fuel	Access.
LBS					
HD270	VP V8-350CE/DI/DP/EVC	4200	1000	420	250
KG					
HD270	VP V8-350CE/DI/DP/EVC	1900	454	190	113



PERFORMANCE

Power HP/KW	Propeller (Dia x Pitch)		Type	Top Speed		Cruise Range	
	IN	CM		MPH	KPH	MI	KM
MC 6.2L 300/B3	26	66	SST	45-48	72-77	175	282
MC 6.2L 350/B3	26	66	SST	47-50	76-81	175	282
MC 6.2L 350/B3/DTS	26	66	SST	47-50	76-81	175	282
MC 6.2L 350/B3/SC/DTS	26	66	SST	47-50	76-81	175	282
MC 8.2MPI/B3/DTS	26	66	SST	50-53	81-85	175	282
VP V8-300C/DI/DP	FH4	FH4	SST	45-48	72-77	185	298
VP V8-350C/DI/DP	FH5	FH5	SST	48-51	77-82	185	298
VP V8-350CE/DI/DP/EVC	FH5	FH5	SST	48-51	77-82	185	298
VP V8-350CE/DI/OX/EVC	FH5	FH5	SST	48-51	77-82	185	298
VP V8 380CE/DP/EVC	FH5	FH5	SST	50-53	81-85	180	298

FUEL FLOW DATA - HD270 MC 6.2L 300/B3

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	9	14	4	15
2500RPM	11	18	7	26
3000RPM	19	31	8	30
3500RPM	27	43	10	38
4000RPM	32	52	12	45
4500RPM	38	61	16	60
5000RPM	43	69	21	79
WOT	47	76	24	91

FUEL FLOW DATA - HD270 MC 6.2L 350/B3/DTS

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	9	14	4	15
2500RPM	11	18	7	26
3000RPM	19	31	8	30
3500RPM	27	43	10	38
4000RPM	33	53	12	45
4500RPM	39	63	17	64
5000RPM	45	72	22	83
WOT	49	79	26	98

FUEL FLOW DATA - HD270 MC 6.2L 350/B3/SC/DTS

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	9	14	4	15
2500RPM	11	18	7	26
3000RPM	19	31	8	30
3500RPM	27	43	10	38
4000RPM	33	53	12	45
4500RPM	39	63	17	64
5000RPM	45	72	22	83
WOT	49	79	26	98

**FUEL FLOW DATA - HD270 MC 6.2L 350/B3**

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	9	14	4	15
2500RPM	11	18	7	26
3000RPM	19	31	8	30
3500RPM	27	43	10	38
4000RPM	33	53	12	45
4500RPM	39	63	17	64
5000RPM	45	72	22	83
WOT	49	79	26	98

FUEL FLOW DATA - HD270 MC 8.2MPI/B3X/DTS

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	11	18	7	27
2500RPM	20	32	9	34
3000RPM	29	47	12	45
3500RPM	36	58	16	61
4000RPM	43	69	20	76
4500RPM	49	79	25	95
WOT	52	84	29	110

FUEL FLOW DATA - HD270 VP V8-300C/DI/DP

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	8	13	3	11
2500RPM	9	14	5	19
3000RPM	13	21	8	30
3500RPM	23	37	8	30
4000RPM	29	47	9	34
4500RPM	35	56	12	45
5000RPM	39	63	16	60
5500RPM	43	69	20	76
WOT	47	76	23	87

FUEL FLOW DATA - HD270 VP V8-350C/DI/DP

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	8	13	3	11
2500RPM	9	14	5	19
3000RPM	13	21	8	30
3500RPM	23	37	8	30
4000RPM	29	47	9	34
4500RPM	36	58	12	45
5000RPM	40	64	17	64
5500RPM	45	72	22	83
WOT	49	79	26	98

**FUEL FLOW DATA - HD270 VP V8-350CE/DI/DP/EVC**

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	8	13	3	11
2500RPM	9	14	5	19
3000RPM	13	21	8	30
3500RPM	23	37	8	30
4000RPM	29	47	9	34
4500RPM	36	58	12	45
5000RPM	40	64	17	64
5500RPM	45	72	22	83
WOT	49	79	26	98

FUEL FLOW DATA - HD270 VP V8-350CE/DI/OX/EVC

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	8	13	3	11
2500RPM	9	14	5	19
3000RPM	13	21	8	30
3500RPM	23	37	8	30
4000RPM	29	47	9	34
4500RPM	36	58	12	45
5000RPM	40	64	17	64
5500RPM	45	72	22	83
WOT	49	79	26	98

FUEL FLOW DATA - HD270 VP V8-380CE/DP/EVC

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	8	13	4	15
2500RPM	11	18	6	23
3000RPM	17	27	8	30
3500RPM	26	42	9	34
4000RPM	30	48	11	42
4500RPM	35	56	14	53
5000RPM	40	64	19	72
5500RPM	45	72	25	95
WOT	51	82	28	106

Performance and Fuel Flows may vary widely due to Boat Weight, Load, Atmospheric Conditions, Engine Conditions, Weight Distribution, Sea Conditions, Propeller, Boat Bottom Condition, Trim Angle and Operator Technique



HD 270 OB

Includes RS & SS

SPECIFICATIONS*	US	METRIC
LLOA	26'5"	8.04 m
Beam	8'5"	2.57 m
Fuel Capacity	70 gal	265 l
Draft (drive up)	16"	41 cm
Draft (drive down)	32"	81 cm
Maximum Capacity	Yacht	Yacht
Persons Capacity	Yacht	12 CE
Approx. Boat & Engine Weight	5130 lbs	2327 kg
Deadrise	20°	20°
Storage Length on Trailer	29'1"	8.87 m
Bridge Clearance	4'9"	1.45 m
Bridge Clearance RS/SS	4'4"	1.32 m
Bridge Clearance with Arch/Tower	7'8"	2.34 m
Total Height	6'5"	1.96 m
Total Height RS/SS	6'0"	1.83 m
Total Height on Trailer	8'3"	2.52 m
Total Height on Trailer RS/SS	7'10"	2.39 m
Height on Trailer w/Wakeboard Tower Dn	9'9"	2.97 m
Height on Trailer w/Wakeboard Tower Up	11'3"	3.43 m
Potable Water	12 gal	45 l

POWER RATINGS & WEIGHTS

Engine Type	Propshaft Power		Boat & Engine Weights	
	HP	KW	LBS	KG
EVINRUDE E250X G2	250	187	5020	2280
EVINRUDE E300XU G2	300	224	5020	2280
MERCURY 250XL VERADO	250	187	5110	2320
MERCURY 300XL VERADO	300	224	5110	2320
MERCURY 350XL VERADO	350	261	5140	2330
YAMAHA F250XCA	250	187	5030	2280
YAMAHA F300XCA	300	224	5030	2280

RECOMMENDED ENGINE(S)/EQUIPMENT AVG. WEIGHTS

Model	Eng. Type	Boat	Eng.	Fuel	Access.
LBS					
HD270 OB	MERC 300XL VERADO	4480	660	420	200
KG					
HD270 OB	MERC 300XL VERADO	2030	299	190	91



PERFORMANCE

Power HP/KW	Propeller (Dia x Pitch)		Type	Top Speed		Cruise Range	
	IN	CM		MPH	KPH	MI	KM
EVINRUDE E250X G2	17	43	SST	45-48	72-77	170	270
EVINRUDE E300XU G2	18	46	SST	49-52	79-84	170	270
MERCURY 250XL VERADO	17	43	SST	45-48	72-77	160	260
MERCURY 300XL VERADO	19	48	SST	49-52	79-84	160	260
MERCURY 350XL VERADO	19	48	SST	52-55	84-89	160	260
YAMAHA F250XCA	17	43	SST	45-48	72-77	160	260
YAMAHA F300XCA	19	48	SST	49-52	79-84	160	260

FUEL FLOW DATA - HD270 OB-E250X G2

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	8	13	3	11
2500RPM	9	14	5	19
3000RPM	10	16	7	26
3500RPM	12	19	9	34
4000RPM	26	42	10	38
4500RPM	33	53	12	45
5000RPM	38	61	14	53
5500RPM	42	68	17	64
WOT	45	72	20	76

FUEL FLOW DATA - HD270 OB-E300XU G2

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	8	13	3	11
2500RPM	9	14	5	19
3000RPM	10	16	7	26
3500RPM	13	21	9	34
4000RPM	27	43	10	38
4500RPM	35	56	13	49
5000RPM	40	64	15	57
5500RPM	44	71	18	68
WOT	48	77	24	91

FUEL FLOW DATA - HD270 OB-250XL VERADO

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	7	11	3	11
2500RPM	8	13	5	19
3000RPM	9	14	6	23
3500RPM	10	16	8	30
4000RPM	25	40	9	34
4500RPM	30	48	11	42
5000RPM	34	55	13	49
5500RPM	38	61	16	60
6000RPM	42	68	18	68
WOT	45	72	20	76

**FUEL FLOW DATA - HD270 OB-300XL VERADO**

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	7	11	3	11
2500RPM	8	13	5	19
3000RPM	10	16	6	23
3500RPM	11	18	8	30
4000RPM	27	43	10	38
4500RPM	32	52	13	49
5000RPM	36	58	15	57
5500RPM	40	64	19	72
6000RPM	45	72	21	79
WOT	48	77	24	91

FUEL FLOW DATA - HD270 OB-350XL VERADO

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	7	11	3	11
2500RPM	9	14	5	15
3000RPM	11	18	6	23
3500RPM	12	19	9	34
4000RPM	29	47	11	42
4500RPM	34	55	15	57
5000RPM	38	61	18	68
5500RPM	43	69	22	83
6000RPM	48	77	25	95
WOT	51	82	28	106

FUEL FLOW DATA - HD270 OB-F250XCA

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	8	13	3	11
2500RPM	9	14	5	19
3000RPM	10	16	7	26
3500RPM	13	21	9	34
4000RPM	27	43	11	42
4500RPM	34	55	13	49
5000RPM	39	63	15	57
5500RPM	42	68	17	64
WOT	45	72	20	76

**FUEL FLOW DATA - HD270 OB-F300XCA**

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	8	13	3	11
2500RPM	9	14	5	19
3000RPM	10	16	7	26
3500RPM	14	23	9	34
4000RPM	29	47	11	42
4500RPM	36	58	14	53
5000RPM	42	68	16	60
5500RPM	45	72	18	68
WOT	48	77	24	91

Performance and Fuel Flows may vary widely due to Boat Weight, Load, Atmospheric Conditions, Engine Conditions, Weight Distribution, Sea Conditions, Propeller, Boat Bottom Condition, Trim Angle and Operator Technique



VISTA SERIES

VISTA 255

SPECIFICATIONS*

	US	METRIC
LOA	25'2"	7.67 m
LOA w/Extended Swim Platform	26'7"	7.92 m
Beam	8'5"	2.55 m
Fuel Capacity	70 gal	265 L
Draft (drive up)	22"	56 cm
Draft (drive down)	36"	91 cm
Maximum Capacity	2100 lbs	953 kg
Persons Capacity	9	9
Approx. Boat & Engine Weight	6175 lbs	2801 kg
Trailer Weight	1600 lbs	735 kg
Deadrise	17°	17°
Bridge Clearance	6'8"	2.03 m
Bridge Clearance w/Arch (excl. electronics)	9'4"	2.84 m
Total Height	8'1"	2.46 m
Total Height w/Arch (excl. electronics)	10'9"	3.28 m
Potable Water	21 gal	79 L
Holding Tank	13 gal	49 L
Generator, Gas	3.5 kw	3.5 kw
Air Conditioning/Heater (Cabin)	9K BTU	9K BTU
Headroom (max)	6'3"	1.90 m
Maximum Sleeping Depth (V-Berth)	6'8"	2.03 m
Maximum Sleeping Width (V-Berth)	4'	1.22 m
Maximum Sleeping Depth (Mid Cabin)	6'11"	2.11 m
Maximum Sleeping Width (Mid Cabin)	4'6"	1.37 m

POWER RATINGS & WEIGHTS

Engine Type	Propshaft Power HP	KW	Boat & Engine Weights LBS	KG
MC 4.5L 250/B3	250	187	6600	2990
MC 6.2L 300/B3	300	224	6700	3040
VP V6-240/DI/DP	240	179	6400	2900
VP V6-280/DI/DP	280	209	6400	2900
VP V8-300/DI/DP	300	224	6500	2950

RECOMMENDED ENGINE(S)/EQUIPMENT AVG. WEIGHTS

Model	Eng. Type	Boat	Eng.	Fuel	Access.
LBS					
V255	VP V8-300/DI/DP	5500	1000	420	450
KG					
V255	VP V8-300/DI/DP	2490	454	190	200

PERFORMANCE

Power HP/KW	Propeller (Dia x Pitch)		Type	Top Speed		Cruise Range	
	IN	CM		MPH	KPH	MI	KM
MC 4.5L 250/B3	22 1/2"	57	SST	38-41	61-66	150	240
MC 6.2L 300/B3	22 1/2"	57	SST	41-44	66-71	150	240
VP V6-240/DI/DP	FH3	FH3	SST	38-41	61-66	160	260
VP V6-280/DI/DP	FH3	FH3	SST	39-42	63-68	160	260
VP V8-300/DI/DP	FH4	FH4	SST	41-44	66-71	160	260

FUEL FLOW DATA - V255 W/MC 4.5L 250/B3

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	8	13	3	11
2500RPM	9	14	6	23
3000RPM	12	19	9	34
3500RPM	22	35	10	38
4000RPM	29	47	12	45
4500RPM	34	55	15	57
5000RPM	39	63	19	72
WOT	40	64	20	76

FUEL FLOW DATA - V255 W/MC 6.2L 300/B3

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	8	13	3	11
2500RPM	9	14	6	23
3000RPM	13	21	12	45
3500RPM	23	37	13	49
4000RPM	32	52	15	57
4500RPM	37	60	18	68
5000RPM	42	68	21	75
WOT	43	69	23	87

FUEL FLOW DATA - V255 W/VP V6-240/DI/DP

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	8	13	3	11
2500RPM	9	15	5	19
3000RPM	10	16	8	30
3500RPM	14	23	11	42
4000RPM	23	37	11	42
4500RPM	30	48	12	45
5000RPM	35	56	15	57
5500RPM	38	61	18	68
WOT	40	64	20	76



FUEL FLOW DATA - V255 W/VP V6-280/DI/DP

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	8	13	3	11
2500RPM	9	15	5	19
3000RPM	10	16	8	30
3500RPM	14	23	11	42
4000RPM	23	37	11	42
4500RPM	30	48	13	49
5000RPM	35	56	16	61
5500RPM	39	63	20	76
WOT	41	66	22	83

FUEL FLOW DATA - V255 W/VP V8-300/DI/DP

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	8	13	3	11
2500RPM	9	15	5	19
3000RPM	10	16	8	30
3500RPM	14	23	11	42
4000RPM	24	39	11	42
4500RPM	31	50	13	49
5000RPM	36	58	16	61
5500RPM	40	64	21	75
WOT	43	69	23	87

FAST FACTS NOTES

VISTA 275

SPECIFICATIONS*	US	METRIC
LOA	28'0"	8.53 m
Beam	9'2"	2.79 m
Fuel Capacity	85 gal	322 L
Draft (drive up)	22"	56 cm
Draft (drive down)	39"	99 cm
Maximum Capacity	2450 lbs	1100 kg
Persons Capacity	10	10
Approx. Boat & Engine Weight	7800 lbs	2911 kg
Deadrise	18°	18°
Bridge Clearance	6'8"	2.03 m
Bridge Clearance w/Arch (excl. electronics)	8'10"	2.69 m
Total Height	8'6"	2.59 m
Total Height w/Arch (excl. electronics)	10'8"	3.25 m
Potable Water (standard or optional)	25 gal	95 L
Holding Tank	17 gal	68 L
Generator, Gas	4 kw	4 kw
Air Conditioning/Heater (Cabin)	8000 BTU	8000 BTU
Headroom (max)	6'3"	1.91 m
Maximum Sleeping Depth (V-Berth)	6'11"	2.11 m
Maximum Sleeping Width (V-Berth)	7'0"	2.13 m
Maximum Sleeping Depth (Mid Cabin)	6'4"	1.93 m
Maximum Sleeping Width (Mid Cabin)	4'6"	1.37 m

POWER RATINGS & WEIGHTS

Engine Type	Propshaft Power		Boat & Engine Weights	
	HP	KW	LBS	KG
MC 6.2L 300/B3	300	224	7500	3400
MC 6.2L 350/B3	300	224	7500	3400
MC 6.2L 350/B3/DTS	300	224	7500	3400
MC 6.2L 350/B3/DTS/SC	300	224	7500	3400
VP V8-300C/DI/DP	300	224	7300	3310
VP V8-350C/DI/DP	350	261	7300	3310
VP V8-350CE/DI/DP/EVC	350	261	7300	3310
VP V8-380CE/DP/EVC	380	283	7400	3360
VP V8-380CE/DI/OX/EVC	380	283	7400	3360

RECOMMENDED ENGINE(S)/EQUIPMENT AVG. WEIGHTS

Model	Eng. Type	Boat	Eng.	Fuel	Access.
LBS					
V275	VP V8-350CE/DI/DP	6300	1000	510	600
KG					
V275	VP V8-350CE/DI/DP	2860	454	231	272

PERFORMANCE

Power HP/KW	Propeller (Dia x Pitch)		Type	Top Speed		Cruise Range	
	IN	CM		MPH	KPH	MI	KM
MC 6.2L 300/B3	22 1/2"	57	SST	36-39	60-64	160	260
MC 6.2L 350/B3	22 1/2"	57	SST	39-42	64-69	160	260
MC 6.2L 350/B3/DTS	22 1/2"	57	SST	39-42	64-69	160	260
MC 6.2L 350/B3/DTS/SC	22 1/2"	57	SST	39-42	64-69	160	260
VP V8-300/DI/DP	FH3	FH3	SST	37-39	61-64	175	280
VP V8-350/DI/DP	FH4	FH4	SST	39-42	64-69	175	280
VP V8-350/DI/DP/EVC	FH4	FH4	SST	39-42	64-69	175	280
VP V8-350/DI/OX/EVC	FH4	FH4	SST	39-42	64-69	175	280
VP V8-380/DP/EVC	FH4	FH4	SST	40-43	68-71	170	270
VP V8-380/OX/EVC	FH4	FH4	SST	40-43	68-71	170	270

FUEL FLOW DATA - V275 W/MC 6.2L 300/B3

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	8	13	5	19
2500RPM	10	16	7	26
3000RPM	18	29	9	34
3500RPM	26	42	11	42
4000RPM	29	47	14	53
4500RPM	32	52	17	64
5000RPM	35	56	20	76
WOT	38	61	23	87

FUEL FLOW DATA - V275 W/MC 6.2L 350/B3

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	8	13	5	19
2500RPM	10	16	7	26
3000RPM	18	29	9	34
3500RPM	26	42	11	42
4000RPM	30	48	15	57
4500RPM	33	53	19	72
5000RPM	37	60	22	83
WOT	41	66	26	98

FUEL FLOW DATA - V275 W/MC 6.2L 350/B3/DTS

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	8	13	5	19
2500RPM	10	16	7	26
3000RPM	18	29	9	34
3500RPM	26	42	11	42
4000RPM	30	48	15	57
4500RPM	33	53	19	72
5000RPM	37	60	22	83
WOT	41	66	26	98



FUEL FLOW DATA - V275 W/MC 6.2L 350/B3/DTS/SC

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	8	13	5	19
2500RPM	10	16	7	26
3000RPM	18	29	9	34
3500RPM	26	42	11	42
4000RPM	30	48	15	57
4500RPM	33	53	19	72
5000RPM	37	60	22	83
WOT	41	66	26	98

FLOW DATA - V275 W/VP V8-300C/DI/DP

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	8	13	4	15
2500RPM	11	18	6	23
3000RPM	14	23	8	30
3500RPM	18	29	9	34
4000RPM	26	42	9	34
4500RPM	31	50	12	45
5000RPM	34	54	16	60
5500RPM	36	58	20	76
WOT	37	60	23	87

FUEL FLOW DATA - V275 W/VP V8-350C/DI/DP

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	8	13	4	15
2500RPM	11	18	6	23
3000RPM	14	23	8	30
3500RPM	18	29	9	34
4000RPM	26	42	10	38
4500RPM	33	53	13	49
5000RPM	37	60	18	68
5500RPM	39	63	22	83
WOT	41	66	25	95

FUEL FLOW DATA - V275 W/VP V8-350CE/DI/DP/EVC

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	8	13	4	15
2500RPM	11	18	6	23
3000RPM	14	23	8	30
3500RPM	18	29	9	34
4000RPM	26	42	10	38
4500RPM	33	53	13	49
5000RPM	37	60	18	68
5500RPM	39	63	22	83
WOT	41	66	25	95



FUEL FLOW DATA - V275 W/VP V8-350CE/DI/OX/EVC

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	8	13	4	15
2500RPM	11	18	6	23
3000RPM	14	23	8	30
3500RPM	18	29	9	34
4000RPM	26	42	10	38
4500RPM	33	53	13	49
5000RPM	37	60	18	68
5500RPM	39	63	22	83
WOT	41	66	25	95

FUEL FLOW DATA - V275 W/VP V8-380CE/DP/EVC

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	8	13	4	15
2500RPM	11	18	6	23
3000RPM	14	23	8	30
3500RPM	18	29	9	35
4000RPM	26	42	11	42
4500RPM	33	53	14	53
5000RPM	37	60	19	72
5500RPM	40	64	25	95
WOT	43	69	28	106

Performance and Fuel Flows may vary widely due to Boat Weight, Load, Atmospheric Conditions, Engine Conditions, Weight Distribution, Sea Conditions, Propeller, Boat Bottom Condition, Trim Angle and Operator Technique.

VISTA 335

SPECIFICATIONS*

	US	METRIC
LOA	33'0"	10.06 m
Beam	10'9"	3.28 m
Fuel Capacity	170 gal	644 L
Draft (drive up)	26"	66 cm
Draft (drive down)	38"	97 cm
Maximum Capacity	Yacht	Yacht
Persons Capacity	11	11
Approx. Boat & Engine Weight	13100 lbs	5940 kg
Deadrise	19°	19°
Bridge Clearance (excl. electronics)	10'6"	3.20 m
Total Height	12'2"	3.71 m
Potable Water (standard or optional)	35 gal	132 L
Holding Tank	27 gal	104 L
Generator, Gas	5.0 KW @ 110 VAC	5.0 KW @ 110 VAC
Generator, Gas	4.0 KW @ 220 VAC	4.0 KW @ 220 VAC
Air Conditioning/Heater (Cabin)	10000 BTU	10000 BTU
Headroom (max)	6'5"	1.96 m
Maximum Sleeping Depth (V-Berth)	6'8"	2.03 m
Maximum Sleeping Width (V-Berth)	6'2"	1.88 m
Maximum Sleeping Depth (Mid Cabin)	6'0"	1.83 m
Maximum Sleeping Width (Mid Cabin)	4'4"	1.32 m

POWER RATINGS & WEIGHTS

Engine Weights Type	Propshaft Power		Boat & Engine	
	HP	KW	LBS	KG
TWIN MC 6.2L 300/B3/DTS	300	224 KW	12300	5580
TWIN MC 6.2L 300/B3/DTS/JPS	300	224 KW	12300	5580
TWIN MC 6.2L 300/B3/DTS/JPS/SC	300	224 KW	12300	5580
TWIN VP D3-220/DPS/EVC/JOYSTICK	209	154 KW	11800	5350
TWIN VP V8-300CE/DI/DP/EVC	300	224 KW	11900	5400
TWIN VP V8-300CE/DI/OX/EVC/JOYSTICK	300	224 KW	11900	5400
TWIN VP V8-300CE/DI/DP/EVC/JOYSTICK	300	224 KW	11900	5400

RECOMMENDED ENGINE(S)/EQUIPMENT AVG. WEIGHTS

Model	Eng. Type	Boat	Eng.	Fuel	Access.
LBS					
V335	VP V8-300/DI/DP	9880	2020	1020	750
KG					
V335	VP V8-300/DI/DP	4480	916	463	344

PERFORMANCE

Power HP/KW	Propeller (Dia x Pitch)		Type	Top Speed		Cruise Range	
	IN	CM		MPH	KPH	MI	KM
Twin MC 6.2L 300/224/B3/DTS	24"	61	SST	43-46	69-74	220	350
Twin MC 6.2L 300/224/B3/DTS/JPS	24"	61	SST	43-46	69-74	220	350
Twin MC 6.2L 300/224/B3/DTS/JPS/SC	24"	61	SST	43-46	69-74	220	35
Twin VP D3-220/DPS/209/154	F4	F4	SST	38-40	60-64	310	500
Twin VP V8-300CE/224/DI/DP/EVC	F3	F3	SST	42-45	68-72	240	390
Twin VP V8-300CE/224/DI/OX/EVC/JOYSTICK	F3	F3	SST	42-45	68-72	240	390
Twin VP V8-300CE/224/DI/DP/EVC/JOYSTICK	F3	F3	SST	42-45	68-72	240	390

FUEL FLOW DATA - V335 W/TWIN MC 6.2L 300/B3/DTS

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	8	13	9	34
2500RPM	14	23	12	45
3000RPM	23	37	14	53
3500RPM	30	48	17	64
4000RPM	34	55	23	87
4500RPM	38	61	30	113
5000RPM	42	68	39	147
WOT	45	72	46	174

FUEL FLOW DATA - V335 W/TWIN MC 6.2L 300/B3/JPS

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	8	13	9	34
2500RPM	14	23	12	45
3000RPM	23	37	14	53
3500RPM	30	48	17	64
4000RPM	34	55	23	87
4500RPM	38	61	30	113
5000RPM	42	68	39	147
WOT	45	72	46	174

FUEL FLOW DATA - V335 W/TWIN MC 6.2L 300/B3/JPS/SC

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	8	13	9	34
2500RPM	14	23	12	45
3000RPM	23	37	14	53
3500RPM	30	48	17	64
4000RPM	34	55	23	87
4500RPM	38	61	30	113
5000RPM	42	68	39	147
WOT	45	72	46	174

**FUEL FLOW DATA - V335 W/TWIN VP D3-220/DPS/209**

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	10	16	8	30
2500RPM	13	21	13	49
3000RPM	25	40	13	49
3500RPM	33	53	16	60
4000RPM	38	61	22	83
WOT	39	63	25	95

FUEL FLOW DATA - V335 W/TWIN VP V8-300CE/DI/DP/EVC

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	8	13	6	23
2500RPM	9	14	10	38
3000RPM	13	21	15	57
3500RPM	23	37	16	60
4000RPM	29	47	20	76
4500RPM	35	56	25	95
5000RPM	38	52	33	125
5500RPM	42	68	41	155
WOT	44	71	46	174

FUEL FLOW DATA - V335 W/TWIN VP V8-300CE/DI/OX/EVC/JOYSTICK

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	8	13	6	23
2500RPM	9	14	10	38
3000RPM	13	21	15	57
3500RPM	23	37	16	60
4000RPM	29	47	20	76
4500RPM	35	56	25	95
5000RPM	38	52	33	125
5500RPM	42	68	41	155
WOT	44	71	46	174

FUEL FLOW DATA - V335 W/TWIN VP V8-300/DI/DP/EVC/JOYSTICK

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	8	13	6	23
2500RPM	9	14	10	38
3000RPM	13	21	15	57
3500RPM	23	37	16	60
4000RPM	29	47	20	76
4500RPM	35	56	25	95
5000RPM	38	52	33	125
5500RPM	42	68	41	155
WOT	44	71	46	174

Performance and Fuel Flows may vary widely due to Boat Weight, Load, Atmospheric Conditions, Engine Conditions, Weight Distribution, Sea Conditions, Propeller, Boat Bottom Condition, Trim Angle and Operator Technique.

FAST FACTS NOTES



VISTA 355

SPECIFICATIONS* US METRIC

LOA	35'0"	10.67 m
Beam	11'6"	3.51 m
Fuel Capacity	200 gal	757 L
Draft (drive up)	28"	71 cm
Draft (drive down)	40"	102 cm
Maximum Capacity	Yacht	Yacht
Persons Capacity	11	11
Approx. Boat & Engine Weight	13850 lbs	6280 kg
Deadrise	19°	19°
Bridge Clearance (excl. electronics)	10'2"	3.10 m
Total Height	12'2"	3.71 m
Potable Water (standard or optional)	45 gal	170 L
Holding Tank	30 gal	113 L
Generator, Gas	5.0 KW @ 110 VAC	5.0 KW @ 110 VAC
Generator, Gas	4.0 KW @ 220 VAC	4.0 KW @ 220 VAC
Air Conditioning/Heater (Cabin)	12000 BTU	12000 BTU
Headroom (max)	6'8"	2.03 m
Maximum Sleeping Depth (V-Berth)	6'0"	1.83 m
Maximum Sleeping Width (V-Berth)	6'2"	1.88 m
Maximum Sleeping Depth (Mid Cabin)	6'0"	1.83 m
Maximum Sleeping Width (Mid Cabin)	5'6"	1.32 m

POWER RATINGS & WEIGHTS

Engine Type	Propshaft HP	Power KW	Boat & Engine Weights LBS	KG
TWIN MC 6.2L 300/B3/DTS	300	224 KW	13600	6170
TWIN MC 6.2L 300/B3/DTS/JPS	300	224 KW	13600	6170
TWIN MC 6.2L 300/B3/DTS/JPS/SC	300	224 KW	13600	6170
TWIN VP D3-220/DPS/EVC	209	154 KW	13000	5900
TWIN VP V8-300CE/DI/DP/EVC	300	224 KW	13200	5990
TWIN VP V8-300CE/DI/DP/EVC/JOYSTICK	300	224 KW	13200	5990
TWIN VP V8-300CE/DI/OX/EVC/JOYSTICK	300	224 KW	13200	5990

RECOMMENDED ENGINE(S)/EQUIPMENT AVG. WEIGHTS

Model	Eng. Type	Boat	Eng.	Fuel	Access.
LBS					
V355	VP V8-300CE/DI/DP	11580	2020	1200	900
KG					
V355	VP V8-300CE/DI/DP	5250	916	544	408



PERFORMANCE

Power HP/KW	Propeller (Dia x Pitch) IN	CM	Type	Top Speed MPH	KPH	Cruise Range MI	KM
Twin MC 6.2L 300/224/B3/DTS	24"	61	SST	42-45	69-74	230	370
Twin MC 6.2L 300/224/B3/DTS/JPS	24"	61	SST	42-45	69-74	230	370
Twin MC 6.2L 300/224/B3/DTS/JPS/SC	24"	61	SST	42-45	69-74	230	370
Twin VP D3-220/DPS/209/154/EVC	F3	F3	SST	35-38	56-61	320	515
Twin VP V8-300CE/224/DI/DP/EVC	F3	F3	SST	41-44	66-71	260	420
Twin VP V8-300CE/224/DI/DP/EVC/JOYSTICK	F3	F3	SST	41-44	66-71	260	420
Twin VP V8-300CE/224/DI/OX/EVC/JOYSTICK	F3	F3	SST	41-44	66-71	260	420

FUEL FLOW DATA - V355 W/TWIN MC 6.2L 300/B3/DTS

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	8	13	9	34
2500RPM	14	23	12	45
3000RPM	23	37	14	53
3500RPM	30	48	17	64
4000RPM	34	55	23	87
4500RPM	38	61	30	113
5000RPM	42	68	39	147
WOT	44	71	46	174

FUEL FLOW DATA - V355 W/TWIN MC 6.2L 300/B3/JPS

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	8	13	9	34
2500RPM	14	23	12	45
3000RPM	23	37	14	53
3500RPM	30	48	17	64
4000RPM	34	55	23	87
4500RPM	38	61	30	113
5000RPM	42	68	39	147
WOT	44	71	46	174

FUEL FLOW DATA - V355 W/TWIN MC 6.2L 300/B3/JPS/SC

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	8	13	9	34
2500RPM	14	23	12	45
3000RPM	23	37	14	53
3500RPM	30	48	17	64
4000RPM	34	55	23	87
4500RPM	38	61	30	113
5000RPM	42	68	39	147
WOT	44	71	46	174

**FUEL FLOW DATA - V355 W/ TWIN VP D3-220/DPS/209**

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	9	14	8	30
2500RPM	12	19	13	49
3000RPM	24	39	13	49
3500RPM	32	52	16	60
4000RPM	36	58	22	83
WOT	37	60	25	95

FUEL FLOW DATA - V355 W/ TWIN VP V8-300CE/DI/DP/EVC

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	8	13	6	23
2500RPM	9	14	10	38
3000RPM	13	21	15	57
3500RPM	23	37	16	60
4000RPM	29	47	20	76
4500RPM	35	56	25	95
5000RPM	38	52	33	125
5500 RPM	41	66	41	155
WOT	43	69	46	174

FUEL FLOW DATA - V355 W/TWIN VP V8-300CE/DI/DP/EVC/JOYSTICK

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	8	13	6	23
2500RPM	9	14	10	38
3000RPM	13	21	15	57
3500RPM	23	37	16	60
4000RPM	29	47	20	76
4500RPM	35	56	25	95
5000RPM	38	52	33	125
5500 RPM	41	66	41	155
WOT	43	69	46	174

FUEL FLOW DATA - V355 W/TWIN VP V8-300CE/DI/OX/EVC/JOYSTICK

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	8	13	6	23
2500RPM	9	14	10	38
3000RPM	13	21	15	57
3500RPM	23	37	16	60
4000RPM	29	47	20	76
4500RPM	35	56	25	95
5000RPM	38	52	33	125
5500 RPM	41	66	41	155
WOT	43	69	46	174

Performance and Fuel Flows may vary widely due to Boat Weight, Load, Atmospheric Conditions, Engine Conditions, Weight Distribution, Sea Conditions, Propeller, Boat Bottom Condition, Trim Angle and Operator Technique.

**FAST FACTS NOTES**

VISTA 375

SPECIFICATIONS*

	US	METRIC
LOA	37'0"	11.28 m
Beam	12'0"	3.66 m
Fuel Capacity	216 gals	818 L
Draft (drive up)	28"	71 cm
Draft (drive down)	40"	102 cm
Maximum Capacity	Yacht	Yacht
Persons Capacity	Yacht	Yacht
Approx. Boat & Engine Weight	14750 lbs	6690 kg
Deadrise	19°	19°
Bridge Clearance (excl. electronics)	10'3"	3.13 m
Total Height	12'5"	3.78 m
Potable Water (standard or optional)	51 gal	193 l
Holding Tank	30 gal	113 l
Generator, Gas	5.0 KW @ 110 VAC	5.0 KW @ 110 VAC
Generator, Gas	4.0 KW @ 220 VAC	4.0 KW @ 220 VAC
Generator, Diesel	6.0 KW @ 110 VAC	6.0 KW @ 110 VAC
Generator, Diesel	4.5 KW @ 220 VAC	4.5 KW @ 220 VAC
Air Conditioning/Heater (Cabin)	16000 BTU	16000 BTU
Headroom (max)	6'4"	1.93 m
Maximum Sleeping Depth (V-Berth)	6'2"	1.88 m
Maximum Sleeping Width (V-Berth)	6'6"	1.98 m
Maximum Sleeping Depth (Mid Cabin)	6'0"	1.83 m
Maximum Sleeping Width (Mid Cabin)	5'6"	1.68 m

POWER RATINGS & WEIGHTS

Engine Weights Type	Propshaft Power		Boat & Engine	
	HP	KW	LBS	KG
TWIN MC 6.2L 350/B3	350	261 KW	14200	6440
TWIN MC 6.2L 350/B3/DTS/JPS	350	261 KW	14200	6440
TWIN MC 6.2L 350/B3/JPS/SC	350	261 KW	14200	6440
TWIN VP D4-260/DPH	250	187 KW	16100	7300
TWIN VP V8-350/DI/DP/EVC	350	261 KW	13800	6260
TWIN VP V8-350/DI/DP/EVC/JOYSTICK	350	2619 KW	13800	6260
TWIN VP V8-350/DI/OX/EVC/JOYSTICK	350	261 KW	13800	6260

RECOMMENDED ENGINE(S)/EQUIPMENT AVG. WEIGHTS

Model	Eng. Type	Boat	Eng.	Fuel	Access.
LBS					
V375	VP V8-350/DI/DP	11800	2020	1380	1000
KG					
V375	VP V8-350/DI/DP	5350	916	626	454

PERFORMANCE

Power HP/KW	Propeller (Dia x Pitch)		Type	Top Speed		Cruise Range	
	IN	CM		MPH	KPH	MI	KM
Twin MC 6.2L/B3/350	24"	61	SST	44-47	71-76	230	370
Twin MC 6.2L/B3/DTS/JPS/350	24"	61	SST	44-47	71-76	230	370
Twin MC 6.2L/B3/JPS/SC/350	24"	61	SST	44-47	71-76	230	370
Twin VP D4-260/DPH/250/184	G5	G5	Nibra	38-40	61-64	330	530
Twin VP V8-350/DI/DP/EVC	FH5	FH5	SST	44-47	71-76	260	420
Twin VP V8-350/DI/DP/EVC/JOYSTICK	FH5	FH5	SST	44-47	71-76	260	420
Twin VP V8-350/DI/OX/EVC/JOYSTICK	FH5	FH5	SST	44-47	71-76	260	420

FUEL FLOW DATA - V375 W/TWIN MC 6.2L 350/B3/DTS

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	9	14	8	30
2500RPM	16	26	14	53
3000RPM	25	40	20	76
3500RPM	32	52	25	95
4000RPM	37	60	30	113
4500RPM	41	66	37	140
5000RPM	44	71	45	170
WOT	46	74	52	197

FUEL FLOW DATA - V375 W/ TWIN MC 6.2L 350/B3/DTS/JPS

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	9	14	8	30
2500RPM	16	26	14	53
3000RPM	25	40	20	76
3500RPM	32	52	25	95
4000RPM	37	60	30	113
4500RPM	41	66	37	140
5000RPM	44	71	45	170
WOT	46	74	52	197

FUEL FLOW DATA - V375 W/ TWIN MC 6.2L 350/B3/JPS/SC

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000RPM	9	14	8	30
2500RPM	16	26	14	53
3000RPM	25	40	20	76
3500RPM	32	52	25	95
4000RPM	37	60	30	113
4500RPM	41	66	37	140
5000RPM	44	71	45	170
WOT	46	74	52	197



H180 SINGLE AXLE TRAILER

(Model #ME H180)

Trailer length w/ Tongue	20'1"	6.121 M
Trailer length w/ Tongue Folded	17'11"	5.461 M
Width	8'2"	2.489 M
Empty Weight w/ Spare	639 LBS	290 KG
Carrying Capacity	2,861 LBS	1298 KG
GVWR (Gross Vehicle Weight Rating)	3,500 LBS	1,587 KG
GAWR (Gross Axle Weight Rating)	3,500 LBS	1,587 KG
Tire Size / Range (Standard)	ST 205/75R14C RADIAL	ST 205/75R14C RADIAL
Tire Size / Range (Rugged Tow)	ST 215/75R14-C	ST 215/75R14-C
Tire Pressure (standard)	50 PSI COLD	350 KPA COLD
Tire Pressure (Rugged Tow)	50 PSI COLD	350 KPA COLD
Tire Capacity (Standard)	1,760 LBS	798 KG
Tire capacity (Rugged Tow)	1,870 LBS	848 KG
Lug Nut Torque	90-120 FT/LBS	120.6NM-162.8NM
Axle	SINGLE	SINGLE
Axle Rating (Per Axle)	3,500 LBS	1,588KG
Hub	5 LUG 4.5" PATTERN	5 LUG 11 CM PATTERN
Wheel Type	SILVER	SILVER
Jack Capacity	1,200 LBS	544 KG
Winch	1,800 LBS	818 KG
Ball Size	2"	5 CM
Ball Towing Height	21"	53.3 CM
Ball Towing Height (Rugged Tow)	22.5"	57 CM



H180 OB SINGLE AXLE TRAILER

(Model #MF H180 OB)

Trailer length w/ Tongue	20'1"	6.121 M
Trailer length w/ Tongue Folded	17'11"	5.461 M
Width	8'2"	2.489 M
Empty Weight w/ Spare	861 LBS	390 KG
Carrying Capacity	3,539 LBS	1,606 KG
GVWR (Gross Vehicle Weight Rating)	4,400 LBS	1,996 KG
GAWR (Gross Axle Weight Rating)	4,400 LBS	1,996 KG
Tire Size / Range (Standard)	ST 225/75R15D RADIAL	ST 225/75R15D RADIAL
Tire Size / Range (Rugged Tow)	ST 225/75R15-E	ST 225/75R15-E
Tire Pressure (Standard)	65 PSI COLD	450 KPA COLD
Tire Pressure (Rugged Tow)	80 PSI COLD	550 KPA COLD
Tire Capacity (Standard)	2,540 LBS	1,152 KG
Tire Capacity (Rugged Tow)	2,830 LBS	1,283 KG
Lug Nut Torque	90-120 FT/LBS	120.6NM-162.8NM
Axle	SINGLE	SINGLE
Axle Rating (Per Axle)	5,000 LBS	1,996 KG
Hub	6 LUG 5.5" PATTERN	6 LUG 14 CM PATTERN
Wheel Type	SILVER	SILVER
Jack Capacity	1,200 LBS	544 KG
Winch	1,800 LBS	818 KG
Ball Size	2"	5 CM
Ball Towing Height	24"	61 CM
Ball Towing Height (Rugged Tow)	24"	61 CM



H190 SINGLE AXLE TRAILER

(Model #MD H190)

Trailer length w/ Tongue	20'1"	6.121 M
Trailer length w/ Tongue Folded	17'11"	5.461 M
Width	8'2"	2.489 M
Empty Weight w/ Spare	861 LBS	390 KG
Carrying Capacity	4139 LBS	1877 KG
GVWR (Gross Vehicle Weight Rating)	5,000 LBS	2,268 KG
GAWR (Gross Axle Weight Rating)	5,000 LBS	2,268 KG
Tire Size / Range (Standard)	ST 225/75R15D RADIAL	ST 225/75R15D RADIAL
Tire Size / Range (Rugged Tow)	ST 225/75R15-E	ST 225/75R15-E
Tire Pressure (standard)	65 PSI COLD	450 KPA COLD
Tire Pressure (Rugged Tow)	80 PSI COLD	550 KPA COLD
Tire Capacity (Standard)	2,540 LBS	1,152 KG
Tire capacity (Rugged Tow)	2,830 LBS	1,283 KG
Lug Nut Torque	90-120 FT/LBS	120.6NM-162.8NM
Axle	SINGLE	SINGLE
Axle Rating (Per Axle)	5,000 LBS	1,996 KG
Hub	6 LUG 5.5" PATTERN	6 LUG 14 CM PATTERN
Wheel Type	SILVER	SILVER
Jack Capacity	1,200 LBS	544 KG
Winch	1,800 LBS	818 KG
Ball Size	2"	5 CM
Ball Towing Height	24"	61 CM
Ball Towing Height (Rugged Tow)	24"	61 CM



H190 TANDEM AXLE TRAILER

(Model #MD H190)

Trailer length w/ Tongue	20'1"	6.121 M
Trailer length w/ Tongue Folded	17'11"	5.461 M
Width	8'0"	2.44 M
Empty Weight w/ Spare	1,123 LBS	509 KG
Carrying Capacity	5,877 LBS	2666 KG
GVWR (Gross Vehicle Weight Rating)	7,000 LBS	3,175 KG
GAWR (Gross Axle Weight Rating)	7,000 LBS	3,175 KG
Tire Size / Range (Standard)	ST 205/75R14C RADIAL	ST 205/75R14C RADIAL
Tire Size / Range (Rugged Tow)	ST 215/75R14-C	ST 215/75R14-C
Tire Pressure (Standard)	50 PSI COLD	350 KPA COLD
Tire Pressure (Rugged Tow)	50 PSI COLD	350 KPA COLD
Tire Capacity (Standard)	1,760 LBS	798 KG
Tire Capacity (Rugged Tow)	1,870 LBS	848 KG
Lug Nut Torque	90-120 FT/LBS	120.6NM-162.8NM
Axle	TANDEM	TANDEM
Axle Rating (Per Axle)	3,500 LBS	1,588 KG
Hub	5 LUG 4.5" PATTERN	5 LUG 11 CM PATTERN
Wheel Type	SILVER	SILVER
Jack Capacity	1,500 LBS	680 KG
Winch	1,800 LBS	818 KG
Ball Size	2"	5 CM
Ball Towing Height	21"	53.3 CM
Ball Towing Height (Rugged Tow)	22.5"	57 CM



H200 SINGLE AXLE TRAILER

(Model #MW H200)

Trailer length w/ Tongue	20'1"	6.12 M
Trailer length w/ Tongue Folded	17'11"	5.461 M
Width	8'6"	2.59 M
Empty Weight w/ Spare	894 LBS	405.5 KG
Carrying Capacity	4,106 LBS	1,862 KG
GVWR (Gross Vehicle Weight Rating)	5,000 LBS	2,268 KG
GAWR (Gross Axle Weight Rating)	5,000 LBS	2,268 KG
Tire Size / Range (Standard)	ST 225/75R15D RADIAL	ST 225/75R15D RADIAL
Tire Size / Range (Rugged Tow)	ST 225/75R15-E	ST 225/75R15-E
Tire Pressure (Standard)	65 PSI COLD	450 KPA COLD
Tire Pressure (Rugged Tow)	80 PSI COLD	550 KPA COLD
Tire Capacity (Standard)	2,540 LBS	1,152 KG
Tire Capacity (Rugged Tow)	2,830 LBS	1,283 KG
Lug Nut Torque	90-120 FT/LBS	120.6 NM-162.8NM
Axle	SINGLE	SINGLE
Axle Rating (Per Axle)	5,000 LBS	2,268 KG
Hub	6 LUG 5.5" PATTERN	6 LUG 14 CM PATTERN
Wheel Type	SILVER	SILVER
Jack Capacity	1,200 LBS	544 KG
Winch	1,800 LBS	818 KG
Ball Size	2"	5 CM
Ball Towing Height	24"	61 CM
Ball Towing Height (Rugged Tow)	24"	61 CM



H200 TANDEM AXLE TRAILER

(Model #MW H200)

Trailer length w/ Tongue	20'1"	6.12 M
Trailer length w/ Tongue Folded	17'11"	5.461 M
Width	8'6"	2.59 M
Empty Weight w/ Spare	1,101 LBS	499.4 KG
Carrying Capacity	5,899 LBS	2676 KG
GVWR (Gross Vehicle Weight Rating)	7,000 LBS	3,175 KG
GAWR (Gross Axle Weight Rating)	7,000 LBS	3,175 KG
Tire Size / Range (Standard)	ST 205/75R14C RADIAL	ST 205/75R14C RADIAL
Tire Size / Range (Rugged Tow)	ST 215/75R14-C	ST 215/75R14-C
Tire Pressure (Standard)	50 PSI COLD	350 KPA COLD
Tire Pressure (Rugged Tow)	50 PSI COLD	350 KPA COLD
Tire Capacity (Standard)	1,760 LBS	798 KG
Tire Capacity (Rugged Tow)	1,870 LBS	848 KG
Lug Nut Torque	90-120 FT/LBS	120.6NM-162.8NM
Axle	TANDEM	TANDEM
Axle Rating (Per Axle)	3,500 LBS	1,588 KG
Hub	5 LUG 4.5" PATTERN	5 LUG 11CM PATTERN
Wheel Type	SILVER	SILVER
Jack Capacity	1,500 LBS	680 KG
Winch	1,800 LBS	818 KG
Ball Size	2"	5 CM
Ball Towing Height	21"	53.3 CM
Ball Towing Height (Rugged Tow)	22.5"	57 CM



H210 TANDEM AXLE TRAILER

(Model #MT H210)

Trailer length w/ Tongue	24'8"	7.518 M
Trailer length w/ Tongue Folded	22'	6.706 M
Width	8'6"	2.59 M
Empty Weight w/ Spare	1,196 LBS	543 KG
Carrying Capacity	5,804 LBS	2,633 KG
GVWR (Gross Vehicle Weight Rating)	7,000 LBS	3,175 KG
GAWR (Gross Axle Weight Rating)	7,000 LBS	3,175 KG
Tire Size / Range (Standard)	ST 205/75R14C RADIAL	ST 205/75R14C RADIAL
Tire Size / Range (Rugged Tow)	ST 215/75R14-C	ST 215/75R14-C
Tire Pressure (Standard)	50 PSI COLD	350 KPA COLD
Tire Pressure (Rugged Tow)	50 PSI COLD	350 KPA COLD
Tire Capacity (Standard)	1,760 LBS	798 KG
Tire Capacity (Rugged Tow)	1,870 LBS	848 KG
Lug Nut Torque	90-120 FT/LBS	120.6NM-162.8NM
Axle	TANDEM	TANDEM
Axle Rating (Per Axle)	3,500 LBS	1,588 KG
Hub	5 LUG 4.5" PATTERN	5 LUG 11CM PATTERN
Wheel Type	SILVER	SILVER
Jack Capacity	1,500 LBS	680 KG
Winch	1,800 LBS	818 KG
Ball Size	2"	5 CM
Ball Towing Height	21"	53.3 CM
Ball Towing Height (Rugged Tow)	22.5"	57 CM



H230 TANDEM AXLE TRAILER

(Model #MU H230)

Trailer length w/ Tongue	23'10"	7.264 M
Trailer length w/ Tongue Folded	21'2"	6.452 M
Width	8'6"	2.591 M
Empty Weight w/ Spare	1,505 LBS	683 KG
Carrying Capacity	5,495 LBS	2,493 kg
GVWR (Gross Vehicle Weight Rating)	7,000 LBS	3,175 KG
GAWR (Gross Axle Weight Rating)	7,000 LBS	3,175 KG
Tire Size / Range (Standard)	ST 205/75R14C RADIAL	ST 205/75R14C RADIAL
Tire Size / Range (Rugged Tow)	ST 215/75R14-C	ST 215/75R14-C
Tire Pressure (Standard)	50 PSI COLD	350 KPA COLD
Tire Pressure (Rugged Tow)	50 PSI COLD	350 KPA COLD
Tire Capacity	1,760 LBS	798 KG
Tire Capacity (Rugged Tow)	1,870 LBS	848 KG
Lug Nut Torque	90-120 FT/LBS	120.6NM-162.8NM
Axle	TANDEM	TANDEM
Axle Rating (Per Axle)	3,500	1,588 KG
Hub	5 LUG 4.5" PATTERN	5 LUG 11CM PATTERN
Wheel Type	SILVER	SILVER
Jack Capacity	1,500 LBS	680 KG
Winch	2,600 LBS	1,179 KG
Ball Size	2"	5 CM
Ball Towing Height	21"	53.3 CM
Ball Towing Height (Rugged Tow)	22.5"	57 CM



H260 TANDEM AXLE TRAILER

(Model #MY H260)

Trailer length w/ Tongue	28'	8.534 M
Trailer length w/ Tongue Folded	23'4"	7.112 M
Width	8'6"	2.59 M
Empty Weight w/ Spare	1,658 LBS	752 KG
Carrying Capacity	8,142 LBS	3,693 KG
GVWR (Gross Vehicle Weight Rating)	9,800 LBS	4,445 KG
GAWR (Gross Axle Weight Rating)	10,000 LBS	4,535 KG
Tire Size / Range (Standard)	ST 225/75R15D RADIAL	ST 225/75R15D RADIAL
Tire Size / Range (Rugged Tow)	ST 225/75R15-E	ST 225/75R15-E
Tire Pressure (Standard)	65 PSI COLD	450 KPA COLD
Tire Pressure (Rugged Tow)	80 PSI COLD	550 KPA COLD
Tire Capacity (Standard)	2,540 LBS	1,152 KG
Tire Capacity (Rugged Tow)	2,830 LBS	1,283 KG
Lug Nut Torque	90-120 FT/LBS	120.6NM-162.8NM
Axle	TANDEM	TANDEM
Axle Rating (Per Axle)	5,000 LBS	2,268 KG
Hub	6 LUG 5.5" PATTERN	6 LUG 14 CM PATTERN
Wheel Type	SILVER	SILVER
Jack Capacity	1,500 LBS	680 KG
Winch	2,600 LBS	1,179 KG
Ball Size	2 5/16"	6 CM
Ball Towing Height	24.5"	62.23 CM
Ball Towing Height (Rugged Tow)	24.5"	62.23 CM



TS 222 TANDEM AXLE TRAILER

(Model #MS TS222)

Trailer length w/ Tongue	22'10"	6.96 M
Trailer length w/ Tongue Folded	20'2"	6.147 M
Width	8'6"	2.59 M
Empty Weight w/ Spare	1,255 LBS	569 KG
Carrying Capacity	5,635 LBS	2,556 KG
GVWR (Gross Vehicle Weight Rating)	7,000 LBS	3,175 KG
GAWR (Gross Axle Weight Rating)	7,000 LBS	3,175 KG
Tire Size / Range (Standard)	255/45R18 RADIAL	255/45R18 RADIAL
Tire Pressure (Standard)	50 PSI COLD	350 KPA COLD
Tire Capacity (Standard)	1,760 LBS	798 KG
Lug Nut Torque	90-120 FT/LBS	120.6NM-162.8NM
Axle	TANDEM	TANDEM
Axle Rating (Per Axle)	3,500 LBS	1,588 KG
Hub	5 LUG 4.5" PATTERN	5 LUG 11 CM PATTERN
Wheel Type	SILVER	SILVER
Jack Capacity	1,500 LBS	680 KG
Winch	1,800 LBS	818 KG
Ball Size	2"	5 CM
Ball Towing Height	21"	53.3 CM



TS 242 TANDEM AXLE TRAILER

(Model #CL TS242)

Trailer length w/ Tongue	26'	7.925 M
Trailer length w/ Tongue Folded	21'4"	6.502 M
Width	8'6"	2.59 M
Empty Weight w/ Spare	1,509 LBS	684.5 kg
Carrying Capacity	8,382 LBS	3,865 kg
GVWR (Gross Vehicle Weight Rating)	9,000 LBS	4,082 KG
GAWR (Gross Axle Weight Rating)	9,000 LBS	4,082 KG
Tire Size / Range (Standard)	255/55R18 RADIAL	255/55R18 RADIAL
Tire Pressure (Standard)	50 PSI COLD	350 KPA COLD
Tire Capacity (Standard)	2,540 LBS	1,152 KG
Lug Nut Torque	90-120 FT/LBS	120.6NM-162.8NM
Axle	TANDEM	TANDEM
Axle Rating (Per Axle)	4,500 LBS	2,041 KG
Hub	6 LUG 5.5" PATTERN	6 LUG 14 CM PATTERN
Wheel Type	MAG	MAG
Jack Capacity	1,500 LBS	680 KG
Winch	2,600 LBS	1,179 KG
Ball Size	2 5/16"	6 CM
Ball Towing Height	24.5"	62.23 CM



HD 220 TANDEM AXLE TRAILER

(Model #FT HD220)

Trailer length w/ Tongue	22'10"	6.96 M
Trailer length w/ Tongue Folded	20'2"	6.147 M
Width	8'6"	2.59 M
Empty Weight w/ Spare	1,256 LBS	570 KG
Carrying Capacity	5,744 LBS	2,605 KG
GVWR (Gross Vehicle Weight Rating)	7,000 LBS	3,175 KG
GAWR (Gross Axle Weight Rating)	7,000 LBS	3,175 KG
Tire Size / Range (Standard)	ST 205/75R14	ST 205/75R14
Tire Size / Range (Rugged Tow)	ST 215/75R14-C	ST 215/75R14-C
Tire Pressure	50 PSI COLD	350 KPA COLD
Tire Pressure (Rugged Tow)	50 PSI COLD	350 KPA COLD
Tire Capacity (Standard)	1,760 LBS	798 KG
Tire capacity (Rugged Tow)	1,870 LBS	848 KG
Lug Nut Torque	90-120 FT/LBS	120.6NM-162.8NM
Axle	TANDEM	TANDEM
Axle Rating (Per Axle)	3,500 LBS	1,588 KG
Hub	5 LUG 4.5" PATTERN	5 LUG 11 CM PATTERN
Wheel Type	SILVER	SILVER
Jack Capacity	1,600 LBS	726 KG
Winch	1,800 LBS	818 KG
Ball Size	2"	5 CM
Ball Towing Height	21"	63.3 CM
Ball Towing Height (Rugged Tow)	22.5"	57 CM



HD 240 TANDEM AXLE TRAILER

(Model #MY HD240)

Trailer length w/ Tongue	25'5"	7.75 M
Trailer length w/ Tongue Folded	20'9"	6.32 M
Width	8'6"	2.59 M
Empty Weight w/ Spare	1,505 LBS	683 KG
Carrying Capacity	8,295 LBS	3,763 KG
GVWR (Gross Vehicle Weight Rating)	9,800 LBS	4,445 KG
GAWR (Gross Axle Weight Rating)	10,000 LBS	4,535 KG
Tire Size / Range (Standard)	ST 225/75R15D RADIAL	ST 225/75R15D RADIAL
Tire Size / Range (Rugged Tow)	ST 225/75R15-E	ST 225/75R15-E
Tire Pressure (Standard)	65 PSI COLD	450 KPA COLD
Tire Pressure (Rugged Tow)	80 PSI COLD	550 KPA COLD
Tire Capacity (Standard)	2,540 LBS	1,152 KG
Tire Capacity (Rugged Tow)	2,830 LBS	1,283 KG
Lug Nut Torque	90-120 FT/LBS	120.6NM-162.8NM
Axle	TANDEM	TANDEM
Axle Rating (Per Axle)	5,000 LBS	2,268 KG
Hub	6 LUG 5.5" PATTERN	6 LUG 14 CM PATTERN
Wheel Type	SILVER	SILVER
Jack Capacity	1,600 LBS	726 KG
Winch	2,600 LBS	1,179 KG
Ball Size	2 5/16"	6 CM
Ball Towing Height	24.5"	62.23 CM
Ball Towing Height (Rugged Tow)	24.5"	62.23 CM



HD 270 TANDEM AXLE TRAILER

(Model #FT HD270)

Trailer length w/ Tongue	28'	8.534 M
Trailer length w/ Tongue Folded	23'4"	7.112 M
Width	8'6"	2.59 M
Empty Weight w/Spare	1,860 LBS	844 KG
Carrying Capacity	7,940 LBS	3,602 KG
GVWR (Gross Vehicle Weight Rating)	9,800 LBS	4,445 KG
GAWR (Gross Axle Weight Rating)	10,000 LBS	4,535 KG
Tire Size / Range (Standard)	ST 225/75R15D RADIAL	ST 225/75R15D RADIAL
Tire Size / Range (Rugged Tow)	ST 225/75R15-E	ST 225/75R15-E
Tire Pressure	65 PSI COLD	450 KPA COLD
Tire Pressure (Rugged Tow)	80 PSI COLD	550 KPA COLD
Tire Capacity (Standard)	2,540 LBS	1,152 KG
Tire Capacity (Rugged Tow)	2,830 LBS	1,283 KG
Lug Nut Torque	90-120 FT/LBS	120.6NM-162.8NM
Axle	TANDEM	TANDEM
Axle Rating (Per Axle)	5,000 LBS	2,268 KG
Hub	6 LUG 5.5" PATTERN	6 LUG 14 CM PATTERN
Wheel Type	SILVER	SILVER
Jack Capacity	1,500 LBS	680 KG
Winch	2,600 LBS	1,179 KG
Ball Size	2 5/16"	6 CM
Ball Towing Height	24.5"	62.23 CM
Ball Towing Height (Rugged Tow)	24.5"	62.23 CM



V255 TANDEM AXLE TRAILER

(Model #FC V255)

Trailer length w/ Tongue	26'3"	8.00 M
Trailer length w/ Tongue Folded	21'4"	6.50 M
Width	8'6"	2.59 M
Empty Weight w/ Spare	1555LBS	705.3 KG
Carrying Capacity	8245 LBS	3,450 KG
GVWR (Gross Vehicle Weight Rating)	9,800 LBS	4,445 KG
GAWR (Gross Axle Weight Rating)	10,000 LBS	4,535 KG
Tire Size / Range (Standard)	ST 225/75R15D RADIAL	ST 225/75R15D RADIAL
Tire Size / Range (Rugged Tow)	ST 225/75R15-E	ST 225/75R15-E
Tire Pressure	65 PSI COLD	450 KPA COLD
Tire Pressure (Rugged Tow)	80 PSI COLD	550 KPA COLD
Tire Capacity (Standard)	2,540 LBS	1,152 KG
Tire capacity (Rugged Tow)	2,830 LBS	1,283 KG
Lug Nut Torque	90-120 FT/LBS	120.6NM-162.8NM
Axle	TANDEM	TANDEM
Axle Rating (Per Axle)	5,000 LBS	2,268 KG
Hub	6 LUG 5.5" PATTERN	6 LUG 14 CM PATTERN
Wheel Type	SILVER	SILVER
Jack Capacity	1,500 LBS	680 KG
Winch	2,600 LBS	1,179 KG
Ball Size	2 5/16"	6 CM
Ball Towing Height	24.5"	62.23 CM
Ball Towing Height (Rugged Tow)	24.5"	62.23 CM



FAST FACTS NOTES



WINNING EDGE DOMESTIC OWNER PROTECTION PLAN

2017 LIMITED WARRANTY FOUR WINNS FIBERGLASS BOATS AND TRAILERS

Rec Boat Holdings, LLC dba Four Winns ("Four Winns") warrants to you, the first North American retail purchaser of this 2017 model year Four Winns boat and/or trailer or a second North American retail purchaser as noted below ("you"), that it will repair or replace, at its sole discretion, defects in materials or workmanship that occur and are reported to Four Winns, or its factory authorized dealer, within the applicable limited warranty periods, subject to the terms, conditions and exclusions set forth below. Your acceptance of delivery of the warranted Four Winns boat and/or trailer constitutes your acceptance of the terms of this limited warranty. This limited warranty gives you specific legal rights and you may have other rights which may vary from state to state.

This limited warranty is the sole and exclusive express warranty from Four Winns regarding your 2017 Four Winns boat and/or trailer and there are no express warranties which extend beyond those outlined in this limited warranty. There are no implied warranties from Four Winns, unless otherwise required under applicable law, and ALL IMPLIED WARRANTIES (INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE) ARE EXCLUDED AND DISCLAIMED WHERE ALLOWED BY APPLICABLE LAW. ANY IMPLIED WARRANTIES (IF APPLICABLE) ARE LIMITED TO THE MINIMUM PERIOD OF TIME ALLOWED UNDER APPLICABLE LAW. Some states do not allow limitations on how long an implied warranty lasts, so the above limitations may not apply to you.

Coverage Under This Limited Warranty

Trailer Limited Warranty: The limited warranty period runs for one (1) year for defects in the boat's exterior cosmetic gel coat, including cracking, crazing, discoloring and fading, except as noted below.

Exterior Cosmetic Gel Coat Limited Warranty: The limited warranty period runs for one (1) year for defects in the boat's exterior cosmetic gel coat, including cracking, crazing, discoloring and fading, except as noted below.

Non-Structural Parts And Components Limited Warranty: The limited warranty period runs for one (1) year for defects in the boat's non-structural parts and components, except as noted below.

Osmotic Hull Blister Limited Warranty: The limited warranty period to the first North American retail purchaser runs for five (5) years, except as noted below, for osmotic Hull (defined below) blisters on the boat, which are defined as blisters larger than 1/8" diameter and with a depth of 1/16" or greater, which occur on the boat Hull below the waterline. This limited warranty is not transferrable to a second North American retail purchaser.

If the boat is bottom painted or left in water for more than sixty (60) days in any ninety (90) day period, this limited warranty will only apply if a marine barrier coating with proper surface preparation is applied to the boat Hull before it is bottom painted or left in water for more than sixty (60) days in any ninety (90) day period.

In the event of osmotic blistering, Four Winns must approve of any repairs, and their method and cost, **before** the repairs are performed, for this limited warranty to apply. Once any repairs are completed, a marine barrier coating will be applied to the affected Hull surface area(s).

Repairs under this osmotic Hull blister limited warranty are limited to one time. Any repair costs covered under this limited warranty are limited to labor and materials only. They will be paid on a prorated basis, according to the schedule outlined below. The repair costs cannot exceed \$150 (US) per foot of boat length prior to the prorating outlined on the next page:



Osmotic Hull blistering reported to Four Winns:	Amount of repair costs paid:
Less than two (2) years from date of delivery	100%
Two (2) to less than three (3) years from date of delivery	75%
Three (3) to less than four (4) years from date of delivery	50%
Four (4) to five (5) years from date of delivery	25%

The limited warranty period to the first North American retail purchaser runs for the duration of the first North American retail purchaser's period of ownership for Structural Hull or Deck Defects (defined below), except as noted below. The limited warranty period to the second (if applicable) North American retail purchaser runs for ten (10) years for Structural Hull or Deck Defects, except as noted below. For purposes of this limited warranty, the "Hull" shall mean the single fiberglass molded shell and integral structural within the shell, including stringers, floorboards, transom and related structural reinforcements, all of which are below the Hull flange (i.e. gunwale) and the "Deck" shall mean the single fiberglass molded shell and integral fiberglass structural components above the Hull flange (i.e. gunwale). A "Structural Hull or Deck Defect" shall mean a substantial defect in the boat's Hull or Deck, which causes the boat to be unfit or unsafe for use as a pleasure craft under normal operating conditions.

The applicable limited warranty period, for both the First and Second (if applicable) North American retail purchasers, runs from the date of delivery of the boat and/or trailer to the first North American retail purchaser, provided that the boat and/or trailer is delivered to that purchaser within twelve (12) months from the date of its manufacture. For a boat and/or trailer delivered to that purchaser more than twelve (12) months after the date of its manufacture, the limited warranty period runs from the date of its manufacture, not from the date the boat and/or trailer was delivered to that purchaser. For a boat and/or trailer delivered to that purchaser more than twelve (12) months and up to thirty-six (36) months after its date of manufacture, the selling dealer will be required to submit a condition report on the boat and/or trailer with photos to Four Winns before delivery of the boat and/or trailer to that purchaser; Four Winns will then determine and advise what limited warranty coverage remains in effect on the boat and/or the trailer, if any. For a boat and/or trailer delivered to that purchaser more than thirty-six (36) months after the date of its manufacture, only the structural limited warranty on the boat will be in effect; all other limited warranties are voided. All limited warranties run concurrently.

Certain portions of this limited warranty, as noted above, extend only to the first North American retail purchaser. Other portions of this limited warranty, as noted above, may be transferred to a second North American retail purchaser, if the transfer occurs within five (5) years of the boat's and/or trailer's sale to the first North American retail purchaser, for a non-refundable recording fee of \$150 (US), for boats less than twenty (20) feet in length, or \$300 (US), for boats twenty (20) feet or more over in length, provided the second North American retail purchaser purchases the boat and/or trailer from the first North American retail purchaser or an authorized Four Winns dealer. To transfer the limited warranty, the second North American retail purchaser or the authorized Four Winns dealer must send to Four Winns, within fifteen (15) days of the boat's and/or trailer's purchase, at the address noted below, the: 1) first North American retail purchaser's plastic registration card, if available; 2) proof of the purchase; and 3) the non-refundable recording fee made payable to Rec Boat Holdings, LLC dba Four Winns. This limited warranty may only be transferred **once**. Four Winns will confirm all limited warranty transfers, in writing, to the authorized Four Winns dealer and/or second North American retail purchaser via email. Four Winns reserves the right to reject a limited warranty transfer request for a Four Winns boat and/or trailer that has been damaged, neglected or otherwise previously excluded from limited warranty coverage.

THIS LIMITED WARRANTY DOES NOT COVER:

1. A boat and/or trailer purchased from any party other than an authorized Four Winns dealer or the first North American retail purchaser.
2. A boat and/or trailer, including its components, that has been altered or modified so as to adversely affect its operation, performance or durability, as determined by Four Winns, or a boat and/or trailer that has been salvaged, declared a total loss or a constructive total loss for any reason not covered in this limited warranty.
3. Any damage resulting from an accident or impact with another object or any damage caused by an act of nature.



4. Damage, breakage and leakage around windshields, hatches or other designed openings.
5. Boats or trailers that are damaged due to storage or exposure conditions including, but not limited to, sun or cold weather.
6. Engines, power trains, outdrives, jet pumps, controls, propellers, batteries, appliances and other equipment, accessories or components that are not manufactured by Four Winns, whether or not they are warranted by other manufacturers. **Note:** it is the purchaser's responsibility to complete any limited warranty registration procedure that may be applicable to these components.
7. Window glass, mirrors, varnish, paint, fabrics and chromium, stainless steel and other metal finishes.
8. Gel coat fading or discoloration that occurs below or at the water line on the Hull.
9. The original gel surface that has been altered in any way, including by repair, application of any coating other than marine barrier coating or marine barrier coating followed by bottom paint, improper surface preparation for paint or improper or excessive sanding, scraping or sandblasting.
10. The cost of removal or re-installment of parts or disassembly of units to repair or replace components covered by this limited warranty.
11. A boat that has been overpowered, according to the boat's maximum recommended engine horsepower, or overloaded in excess of the maximum limits as stated on the U.S. Coast Guard Capacity Plate.
12. Any boat and/or trailer that has been misused or used in a negligent manner; a boat that has been used for racing, speed or endurance contests; used for rental or charter; used for military, rescue, fire, safety, medical, police, law enforcement, patrol or similar government uses; used for commercial purposes; used without normal maintenance; operated contrary to any instruction furnished by Four Winns; improperly lifted or trailered; improperly secured to a trailer; or operated in violation of any federal, state, local, Coast Guard or other governmental agency laws, rules or regulations. Also, this limited warranty does not cover any damage to a boat resulting from failure to use a lower unit support device when transporting the boat.
13. Estimated characteristics such as weight, speed, range, fuel consumption or other estimated performance characteristics.
14. Dealer preparation, cleaning, final adjustments and alignments in preparing the boat and/or trailer for delivery.
15. Fit and adjustment of exterior canvas tops, enclosures and weather covers or other soft goods.
16. Sacrificial deterioration of anti-fouling paint or zinc anodes.
17. Damage resulting from electrolysis or corrosion of any nature from any source.
18. Any failure or defect arising from previous repairs made by a non-authorized service provider, unless preapproved by Four Winns.
19. Any defect that results in the redesign of the Four Winns boat and/or trailer.
20. Trailer tires, paint or Gatorhyde defects caused by fading, peeling, chipping, scratches or rusting attributed to normal use.

THE SOLE AND EXCLUSIVE REMEDY UNDER THIS LIMITED WARRANTY AND ANY APPLICABLE IMPLIED WARRANTY IS THE REPAIR OR REPLACEMENT, AT FOUR WINNS' SOLE OPTION, OF



WARRANTED PARTS AND COMPONENTS. FOUR WINNS EXCLUDES AND DISCLAIMS ANY LIABILITY FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES, INCLUDING LOSS OF TIME, INCONVENIENCE, INSTALLMENT PAYMENTS, INSURANCE PAYMENTS, MARINA FEES, RETAIL CHARGES, TRAVEL EXPENSES, LOSS OF USE, HAUL OUT, LAUNCH, TOWING AND/OR STORAGE CHARGES, LOSS OF OR DAMAGE TO PERSONAL PROPERTY OR OTHER SIMILAR COSTS AND EXPENSES OR ANY CLAIM NOT SPECIFICALLY COVERED BY THIS LIMITED WARRANTY. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. Any legal action alleging breach of any applicable warranty coverage must be brought within one (1) year from the date the alleged breach first occurred or the shortest period allowed under applicable law, whichever is earlier.

PRE-DELIVERY SERVICE AND LIMITED WARRANTY REGISTRATION

Prior to delivering a new Four Winns boat and/or trailer to the first North American retail purchaser, the authorized dealer is required to inspect and perform all necessary pre-delivery services including completing the "Pre-Delivery Service Record" portion of the limited warranty. Any cost associated with the pre-delivery inspection is the responsibility of the first North American retail purchaser. After completion of the necessary pre-delivery services, the first North American retail purchaser must sign the Four Winns limited warranty registration form and Pre-Delivery Service Record provided by the dealer, where indicated. No limited warranty coverage is applicable to the boat and/or trailer unless these forms are completed, signed and returned to Four Winns at the address indicated below, or via an authorized Four Winns dealer's online dealer extranet. All information received by Four Winns via the limited warranty registration or transfer process shall be the property of Four Winns, and submission of information, directly or indirectly, via the limited warranty registration process shall, to the extent permitted by applicable law, be deemed to constitute consent by the purchaser and dealer to Four Winns's use of such information at any time for all purposes allowed by law, including use of that information by third parties selected by Four Winns. You may opt to not have your personal information disclosed to third parties and/or to not receive marketing materials from Four Winns by sending a written request to: Four Winns Warranty Department, 925 Frisbie Street, Cadillac, MI 49601.

OBTAINING REPAIRS UNDER THIS LIMITED WARRANTY

The authorized Four Winns dealer will carry out the limited warranty procedures on your behalf. All limited warranty work must be performed at an authorized dealer or a sublet repair facility chosen by an authorized dealer, at the Four Winns factory, or at another repair facility approved by The authorized Four Winns dealer will carry out the limited warranty procedures on your behalf. All limited warranty work must be performed at an authorized dealer or a sublet repair facility chosen by an authorized dealer, at the Four Winns factory, or at another repair facility approved by Four Winns. You are responsible for the expense associated with transporting the boat and/or trailer to and from the repair facility. Four Winns must receive written notice of all limited warranty claims prior to the expiration of this limited warranty and be allowed an opportunity to resolve them.

To obtain limited warranty service, you must return the boat and/or trailer, including any alleged defective part, to an authorized Four Winns dealer and present the Owner's Registration Card. If necessary, you should call Four Winns for assistance to locate the nearest Four Winns dealer in your area. The following procedures will apply to a limited warranty claim:

- A. The dealer will contact and receive an authorization number from Four Winns for repairs.
- B. Upon completion of repairs, you must pay the dealer for non-covered items.
- C. You assume all liability for payment of non-authorized repairs.
- D. You must sign the Four Winns limited warranty claim form if the claim is not submitted through the Four Winns extranet by the dealer.

If sublet limited warranty repairs are required for any reason, the authorized Four Winns dealer will be responsible for choosing a qualified and reputable repair facility and the authorized **Four Winns Dealer will be responsible for all work performed by the sublet repair facility. Before referring any work to a sublet repair facility, the authorized Four Winns dealer must submit a written estimate to Four Winns' claims department to obtain written pre-authorization (including a claim authorization number).** Four Winns will not honor or pay for claims submitted for repairs by sublet repair facilities unless this procedure has been followed. Four Winns will not authorize or pay for sublet repairs initiated because of a lack of dealer service facilities.



This document contains the entire limited warranty provided by Four Winns. Any questions concerning the scope of this limited warranty should be directed to Four Winns. The terms and conditions contained in this limited warranty may not be modified, altered, or waived by any action, inaction or representation, whether oral or in writing, except upon the express, written authority of a senior management level employee of Four Winns. Four Winns does not authorize any person or persons (except a senior management level employee of Four Winns), including Four Winns dealers, to change the terms of this limited warranty. (Note that your authorized Four Winns dealer is an independent business, authorized to sell and service Four Winns products, but is not an agent of Four Winns). Four Winns reserves the right to change or improve the design or manufacture of Four Winns boats and/or trailers without obligation to modify any boat and/or trailer previously manufactured.

FOUR WINNS

925 Frisbie Street | Cadillac, MI 49601
(231) 775-1351



WINNING EDGE INTERNATIONAL OWNER PROTECTION PLAN

2017 LIMITED WARRANTY FOUR WINNS FIBERGLASS BOATS

Rec Boat Holdings, LLC dba Four Winns ("Four Winns") warrants to you, the first International retail purchaser of this 2017 model year Four Winns boat or a second International retail purchaser as noted below ("you"), that it will repair or replace, at its sole discretion, defects in materials or workmanship that occur and are reported to Four Winns, or its factory authorized dealer, within the applicable limited warranty periods, subject to the terms, conditions and exclusions set forth below. Your acceptance of delivery of the warranted Four Winns boat constitutes your acceptance of the terms of this limited warranty.

This limited warranty is the sole and exclusive express warranty from Four Winns regarding your 2016 Four Winns boat, and there are no express warranties which extend beyond those outlined in this limited warranty. There are no implied warranties from Four Winns, unless otherwise required under applicable law, and ALL IMPLIED WARRANTIES (INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE) ARE EXCLUDED AND DISCLAIMED WHERE ALLOWED BY APPLICABLE LAW. ANY IMPLIED WARRANTIES (IF APPLICABLE) ARE LIMITED TO THE MINIMUM PERIOD OF TIME ALLOWED UNDER APPLICABLE LAW. Retail purchasers in the European Union (EU) may have legal rights under applicable national legislation and the Consumers Protective Directive 1999/44/EC of the European Parliament and of the Council of 25 May 1999, governing the sale of consumer goods, which are not affected by this limited warranty. Retail purchasers in other countries may also have legal rights which are not affected by this limited warranty.

Coverage Under This Limited Warranty

Exterior Cosmetic Gel Coat Limited Warranty: The limited warranty period runs for one (1) year for defects in the exterior cosmetic gel coat, including cracking, crazing, discoloring and fading, except as noted below.

Non-Structural Parts And Components Limited Warranty: The limited warranty period runs for one (1) year for defects in non-structural parts and components, except as noted below.

Osmotic Hull Blister Limited Warranty: The limited warranty period to the first International retail purchaser runs for five (5) years, except as noted below, for osmotic Hull (defined below) blisters on the boat, which are defined as blisters larger than 1/8" diameter and with a depth of 1/16" or greater, which occur on the boat Hull below the waterline. This limited warranty is not transferrable to a second International retail purchaser.

If the boat is bottom painted or left in water for more than sixty (60) days in any ninety (90) day period, this limited warranty will only apply if a marine barrier coating with proper surface preparation is applied to the boat Hull before it is bottom painted or left in water for more than sixty (60) days in any ninety (90) day period.

In the event of osmotic blistering, Four Winns must approve of any repairs, and their method and cost, **before** the repairs are performed, for this limited warranty to apply. Once any repairs are completed, a marine barrier coating will be applied to the affected Hull surface area(s).

Repairs under this osmotic Hull limited warranty are limited to one time. Any repair costs covered under this limited warranty are limited to labor and materials only. They will be paid on a prorated basis, according to the schedule outlined below. The repair costs cannot exceed \$150 (US) per foot of boat length prior to the prorating outlined below:

Osmotic Hull blistering reported to Four Winns: Amount of repair costs paid:

Less than two (2) years from date of delivery	100%
Two (2) to less than three (3) years from date of delivery	75%
Three (3) to less than four (4) years from date of delivery	50%
Four (4) to five (5) years from date of delivery	25%



Structural Hull or Deck Limited Warranty: The limited warranty period to the first International retail purchaser runs for the duration of the first International retail purchaser's period of ownership for Structural Hull or Deck Defects (defined below), except as noted below. The limited warranty period to the second (if applicable) International retail purchaser runs for ten (10) years for Structural Hull or Deck Defects, except as noted below. For purposes of this limited warranty, the "Hull" shall mean the single fiberglass molded shell and integral structural within the shell, including stringers, floorboards, transom and related structural reinforcements, all of which are below the Hull flange (i.e. gunwale) and the "Deck" shall mean the single fiberglass molded shell and integral fiberglass structural components above the Hull flange (i.e. gunwale). A "Structural Hull or Deck Defect" shall mean a substantial defect in the boat's Hull or Deck, which causes the boat to be unfit or unsafe for use as a pleasure craft under normal operating conditions.

The applicable limited warranty period for both the first and second International retail purchaser runs from the date of delivery of the boat to the first International retail purchaser, provided that the boat is delivered to that purchaser within twelve (12) months from the date of its manufacture. For a boat delivered to that purchaser more than twelve (12) months after the date of its manufacture, the limited warranty period runs from the date of its manufacture, not from the date the boat was delivered to that purchaser. For a boat delivered to that purchaser more than twelve (12) months and up to thirty-six (36) months after its date of manufacture, the selling dealer will be required to submit a condition report on the boat with photos to Four Winns before delivery of the boat to the first International retail purchaser; Four Winns will then determine and advise what limited warranty coverage remains in effect on the boat, if any. For a boat delivered to that purchaser more than thirty-six (36) months after the date of its manufacture, only the structural limited warranty on the boat will be in effect; all other limited warranties are voided. All limited warranties run concurrently.

Certain portions of this limited warranty, as noted above, extend only to the first International retail purchaser. Other portions of this limited warranty, as noted above, may be transferred to a second International retail purchaser, if the transfer occurs within five (5) years of the boat's sale to the first International retail purchaser, for a non-refundable recording fee of \$150 (US), for boats less than twenty (20) feet in length, or \$300 (US), for boats twenty (20) feet or more in length, provided the second International retail purchaser purchases the boat from the first International retail purchaser or an authorized Four Winns dealer. To transfer the limited warranty, the second International retail purchaser or the authorized Four Winns dealer must send to Four Winns, within fifteen (15) days of the boat's purchase, at the address noted below, the: 1) first International retail purchaser's plastic registration card, if available; 2) proof of the purchase; and 3) the non-refundable recording fee made payable to Rec Boat Holdings, LLC dba Four Winns. This limited warranty may only be transferred **once**. Four Winns will confirm all limited warranty transfers, in writing, to the authorized Four Winns dealer and/or second International retail purchaser via email. Four Winns reserves the right to reject a limited warranty transfer request for a Four Winns boat that has been damaged, neglected or otherwise previously excluded from limited warranty coverage.

THIS LIMITED WARRANTY DOES NOT COVER:

1. A boat purchased from any party other than an authorized Four Winns dealer or the first International retail purchaser.
2. A boat, including its components, that has been altered or modified so as to adversely affect its operation, performance or durability, as determined by Four Winns, or a boat that has been salvaged, declared a total loss or a constructive total loss for any reason not covered in this limited warranty.
3. Any damage resulting from an accident or impact with another object or any damage caused by an act of nature.
4. Damage, breakage and leakage around windshields, hatches or other designed openings.
5. Boats that are damaged due to storage or exposure conditions including, but not limited to, sun or cold weather.
6. Engines, power trains, outdrives, jet pumps, controls, propellers, batteries, appliances and other equipment, accessories or components that are not manufactured by Four Winns, whether or not they are warranted by other manufacturers. **Note:** it is the purchaser's responsibility to complete any limited warranty registration procedure that may be applicable to these components.
7. Window glass, mirrors, varnish, paint, fabrics and chromium, stainless steel and other metal finishes.



8. Gel coat fading or discoloration that occurs below or at the water line on the Hull.
9. The original gel surface that has been altered in any way, including by repair, application of any coating other than marine barrier coating or marine barrier coating followed by bottom paint, improper surface preparation for paint or improper or excessive sanding, scraping or sandblasting.
10. The cost of removal or re-installment of parts or disassembly of units to repair or replace components covered by this limited warranty.
11. A boat that has been overpowered, according to the boat's maximum recommended engine horsepower, or overloaded in excess of the maximum limits as stated on the Capacity Plate (if applicable).
12. Any boat that has been misused or used in a negligent manner; that has been used for racing, speed or endurance contests; used for rental or charter; used for military, rescue, fire, safety, medical, police, law enforcement, patrol or similar government uses; used for commercial purposes; used without normal maintenance; operated contrary to any instruction furnished by Four Winns; improperly lifted or trailered; improperly secured to a trailer; or operated in violation of any federal, state, local, or other governmental agency laws, rules or regulations. Also, this limited warranty does not cover any damage to a boat resulting from failure to use a lower unit support device when transporting the boat.
13. Estimated characteristics such as weight, speed, range, fuel consumption or other estimated performance characteristics.
14. Dealer preparation, cleaning, final adjustments and alignments in preparing the boat for delivery.
15. Fit and adjustment of exterior canvas tops, enclosures and weather covers or other soft goods.
16. Sacrificial deterioration of anti-fouling paint or zinc anodes.
17. Damage resulting from electrolysis or corrosion of any nature from any source.
18. Any failure or defect arising from previous repairs made by a non-authorized service provider, unless preapproved by Four Winns.
19. Any defect that results in the redesign of the Four Winns boat.
20. Trailers.

THE SOLE AND EXCLUSIVE REMEDY UNDER THIS LIMITED WARRANTY AND ANY APPLICABLE IMPLIED WARRANTY IS THE REPAIR OR REPLACEMENT, AT FOUR WINNS' SOLE OPTION, OF WARRANTED PARTS AND COMPONENTS. FOUR WINNS EXCLUDES AND DISCLAIMS ANY LIABILITY FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES, INCLUDING LOSS OF TIME, INCONVENIENCE, INSTALLMENT PAYMENTS, INSURANCE PAYMENTS, MARINA FEES, RETAIL CHARGES, TRAVEL EXPENSES, LOSS OF USE, HAUL OUT, LAUNCH, TOWING AND/OR STORAGE CHARGES, LOSS OF OR DAMAGE TO PERSONAL PROPERTY OR OTHER SIMILAR COSTS AND EXPENSES OR ANY CLAIM NOT SPECIFICALLY COVERED BY THIS LIMITED WARRANTY. Any legal action alleging breach of any applicable warranty coverage must be brought within one (1) year from the date the alleged breach first occurred or the shortest period of time allowed under applicable law. Any claim by a retail purchaser in the EU that the boat was nonconforming at the time of delivery must be made within two (2) years from the date of delivery.

PRE-DELIVERY SERVICE AND LIMITED WARRANTY REGISTRATION

Prior to delivering a new Four Winns boat to the first International retail purchaser, the authorized dealer is required to inspect and perform all necessary pre-delivery services including completing the "Pre-Delivery Service Record" portion of the limited warranty. Any cost associated with the pre-delivery inspection is the responsibility of the first International retail purchaser. After completion of the necessary pre-delivery services, the first International retail purchaser must sign the Four Winns limited warranty registration form and Pre-Delivery Service Record provided by the dealer, where indicated. No limited warranty coverage is applicable to the boat unless these forms are completed, signed and returned to Four Winns at the address indicated below, or via an authorized Four Winns dealer's online dealer extranet. All information received by Four Winns via the limited warranty registration or transfer process shall be the property of Four Winns, and submission of information, directly or indirectly, via the limited warranty registration process shall, to the extent



permitted by applicable law, be deemed to constitute consent by the purchaser and dealer to Four Winns' use of such information at any time for all purposes allowed by law, including use of that information by third parties selected by Four Winns. You may opt to not have your personal information disclosed to third parties and/or to not receive marketing materials from Four Winns by sending a written request to: Four Winns Warranty Department, 925 Frisbie Street, Cadillac, MI 49601.

OBTAINING REPAIRS UNDER THIS LIMITED WARRANTY

The authorized Four Winns dealer will carry out the limited warranty procedures on your behalf. All limited warranty work must be performed at an authorized dealer or a sublet repair facility chosen by an authorized dealer, at the Four Winns factory, or at another repair facility approved by Four Winns. You are responsible for the expense associated with transporting the boat to and from the repair facility. Four Winns must receive written notice of all limited warranty claims prior to the expiration of this limited warranty and be allowed an opportunity to resolve them.

To obtain limited warranty service, you must return the boat, including any alleged defective part, to an authorized Four Winns dealer and present the Owner's Registration Card. If necessary, you should call Four Winns for assistance to locate the nearest Four Winns dealer in your area. The following procedures will apply to a warranty claim:

- A. The dealer will contact and receive an authorization number from Four Winns for repairs.
- B. Upon completion of repairs, you must pay the dealer for non-covered items.
- C. You assume all liability for payment of non-authorized repairs.
- D. You must sign the Four Winns limited warranty claim form if the claim is not submitted through the Four Winns extranet by the dealer.

The authorized Four Winns dealer will carry out the limited warranty procedures on your behalf. All limited warranty work must be performed at an authorized dealer or a sublet repair facility chosen by an authorized dealer, at the Four Winns factory, or at another repair facility approved by Four Winns. You are responsible for the expense associated with transporting the boat to and from the repair facility. Four Winns must receive written notice of all limited warranty claims prior to the expiration of this limited warranty and be allowed an opportunity to resolve them.

To obtain limited warranty service, you must return the boat, including any alleged defective part, to an authorized Four Winns dealer and present the Owner's Registration Card. If necessary, you should call Four Winns for assistance to locate the nearest Four Winns dealer in your area. The following procedures will apply to a warranty claim:

- A. The dealer will contact and receive an authorization number from Four Winns for repairs.
- B. Upon completion of repairs, you must pay the dealer for non-covered items.
- C. You assume all liability for payment of non-authorized repairs.
- D. You must sign the Four Winns limited warranty claim form if the claim is not submitted through the Four Winns extranet by the dealer.

If sublet limited warranty repairs are required for any reason, the authorized Four Winns dealer will be responsible for choosing a qualified and reputable repair facility and the authorized **Four Winns Dealer will be responsible for all work performed by the sublet repair facility. Before referring any work to a sublet repair facility, the authorized Four Winns dealer must submit a written estimate to Four Winns' claims department to obtain written pre-authorization (including a claim authorization number).** Four Winns will not honor or pay for claims submitted for repairs by sublet repair facilities unless this procedure has been followed. Four Winns will not authorize or pay for sublet repairs initiated because of a lack of dealer service facilities.

This document contains the entire limited warranty provided by Four Winns. Any questions concerning the scope of this limited warranty should be directed to Four Winns. The terms and conditions contained in this limited warranty may not be modified, altered, or waived by any action, inaction or representation, whether oral or in writing, except upon the express, written authority of a senior management level employee of Four Winns.



Four Winns does not authorize any person or persons (except a senior management level employee of Four Winns), including Four Winns dealers, to change the terms of this limited warranty. (Note that your authorized Four Winns dealer is an independent business, authorized to sell and service Four Winns products, but is not an agent of Four Winns). Four Winns reserves the right to change or improve the design or manufacture of Four Winns boats and/or trailers without obligation to modify any boat and/or trailer previously manufactured.

FOUR WINNS
925 Frisbie Street | Cadillac, MI 49601
(231) 775-1351



FAST FACTS NOTES



925 Frisbie Street | Cadillac, MI 49601
231.775.1351

www.fourwinns.com